TRAP PRIMER TAILPIECE

200/213/206 SERIES

TrapEase™

ITEM # SUBMITTED_____

JOB NAME_____

LOCATION _____

ENGINEER_____

CONTRACTOR_____

PO#_____ TAG _____

SPECIFICATION

Sioux Chief 200/213/206 series TrapEase™ trap Primer tailpiece shall be used where necessary to replenish water-filled traps in drainage systems. Trap primer tailpiece shall be a gravity fed device with no mechanical parts and include a 1/2" nominal branch connection.
Certified to ASSE 1044 and meets applicable drainage requirements set forth by ASSE 1044.

INSTALLATION

Installs between lav/sink drain and trap. Replenishes water in floor drain traps to prevent escape of sewer gas. The number of traps serviced by any trap primer is a function of activation frequency and evaporation rate and should be determined by the design engineer and/or the installing contractor.

MATERIALS[1]

Body / Nut: brass
Arm: copper

DIMENSIONS

	200 Series	213 Series	206 Series
A: Inlet	1-1/2" direct connect	1-1/4" fine thread	1-1/2" slip joint
B: Outlet	1-1/2" tubular	1-1/4" tubular	1-1/2" tubular
C: Arm	1/2" nominal	1/2" nominal	1/2" nominal
D: Height	8"	6"	6"
E: Slip socket	n/a	n/a	2-5/8"

1 Unfinished and chrome-plated options available

200-090

213-092

206-096







ASSE 1044 C UPC ®

Select Item Number

☐ **200-090** = Direct connect - Unfinished
☐ **200-092** = Direct connect - Chrome-plated
☐ **213-090** = Fine thread - Unfinished
☐ **213-092** = Fine thread - Chrome-plated
☐ **206-096** = Slip Joint - Chrome plated