OUTLET BOX FRAME INSERT

696 SERIES

OxBox™

ITEM # SUBMITTED_____

JOB NAME_____

LOCATION _____

ENGINEER_____

CONTRACTOR_____

PO#_____ TAG _____

SPECIFICATION

Sioux Chief 696 series OxBox™ frame inserts shall be used where necessary in accessible plumbing applications. Frame inserts shall fit into the frame of any 696 series OxBox™ outlet box. Louvered frame insert shall allow for air flow to a plumbing device when required. The solid frame insert shall limit access to and conceal the box contents. The solid frame insert with cutout shall allow for supply hoses to be connected to valves inside the box when frame insert is installed.

MATERIALS

ABS

FREE AREA

3.90 in^2 (Louvered insert)

WORKING TEMPERATURE

Melting point: 200°F
Working temperature: 150°F

DIMENSIONS

A:	Width	4"
B:	Height	5-5/8"
C:	Cutout width (696-SC1)	3"
D:	Cutout height (696-SC1)	2"

696-SC

696-LC

696-SC1



Create Item Number

696-A

e.g. 696-LC: OxBox louvered frame insert

COVER OPTION A

☐ **SC** = solid frame insert
☐ **LC** = louvered frame insert
☐ **SC1** = solid frame insert with cutout