/// 131-G SERIES QUARTER-TURN SUPPLY STOPS – STRAIGHT

ITEM # SUBMITTED_____

JOB NAME _____

LOCATION_____

ENGINEER _____

CONTRACTOR _____

PO#_____ TAG _____

SPECIFICATION
Tomahawk 131-G Series Quarter-Turn Supply Stops shall be used as a means of controlling pressure water connections to plumbing fixtures for the purpose of being able to turn off flow for repairs or emergency situations.

INSTALLATION
Attach to pressure piping as prescribed by inlet connection on stop valve. Connect supply hose of desired configuration to outlet of supply.

MATERIALS
Valve body: no lead brass
Ball: chrome-plated brass
Ball seats: polytetrafluoroethylene (P.T.F.E.)
Sleeve: brass
Nut: brass
Finish: chrome

131-G2F1C04

FEATURES
- "kwik" quarter-turn "on" or "off"
- ball valve style construction
- large, conventional handles
- chrome-plated no lead brass construction with PTFE seats
- certified to NSF/ANSI 61 section 9-G
- nuts and ferrules assembled
- IAPMO listed

PACKAGING
Individually boxed or individually bagged

*Custom lengths available in large quantity only. Contact your local rep to confirm availability.

PRESSURE & TEMPERATURE
Maximum pressure: 125psi / 8.6 bar
Maximum temperature: 160°F / 71.1°C

See page 2.

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

/// 131-G SERIES QUARTER-TURN SUPPLY STOPS – STRAIGHT

DIMENSIONS

*Tomahawk specifications in US customary units are approximate are provided for reference only.

	-G1F1C	-G1Q1C	-G2C1C	-G2F1C	-G2F2M	-G2Q1C	-G2S1C
A: handle	1.812"	1.812"	1.812"	1.812"	1.812"	1.812"	1.812"
B: height	0.875"	0.937"	1.062"	1.25"	1.25"	1.25"	1.062"
C: length	1.937"	2.375"	2.375"	2.062"	2"	2.375"	2.5"

	-G2S1CE5	-G2V1C	-G2X1C	-G2X2M	-G2X2X	-GRETR001
A: handle	1.812"	1.812"	1.812"	1.812"	1.812"	1.812"
B: height	2.25"	1.062"	1.062"	1.25"	0.5"	0.875"
C: length	7.625"	2.625"	2.875"	2"	2.187"	2.5"



Straight

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Create Item Number

131-GABCD

e.g. **131-G2S1CE504:** quarter-turn straight supply stop, 1/2" female sweat X 3/8" O.D. compression w/ 5" extension & escutcheon, 1/bx

INLET CONNECTION A
- ☐ **1F** = 3/8" FIP
- ☐ **1Q** = 3/8" PDQ push fit
- ☐ **2C** = 1/2" compression
- ☐ **2F** = 1/2" FIP
- ☐ **2Q** = 1/2" PDQ push fit
- ☐ **2S** = 1/2" female sweat
- ☐ **2V** = 1/2" CPVC
- ☐ **2X** = 1/2" PEX F1807
- ☐ **RETR001** = 3/8" female compression X 3/8" male compression 1/bg

OUTLET CONNECTION B
- ☐ **0C** = 1/4" compression
- ☐ **1C** = 3/8" compression
- ☐ **2M** = 1/2" MIP
- ☐ **2X** = 1/2" PEX F1807

SPECIAL OPTION C
- ☐ _ = standard valve
- ☐ **E5** = 5" extension w/ escutcheon

PACKAGE D
- ☐ **01** = individually bagged
- ☐ **04** = individually boxed

*Not all size and length combinations available. Contact your local rep to confirm availability.