# Product data sheet

Specifications

## Main circuit breaker unit, EZ Meter-Pak, 2000A, 120/240VAC, 1ph/3W, 1200A bus, 65kA, UG, Type 3R, ERMS

EZM12000CBUMS

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | EZ meter-pak |
| **Product or Component Type** | Meter center main unit |
| **Main type** | Main Circuit Breaker |
| **Included Items** | Circuit-breaker 1) 2P 2000 A 65 kA main supply, ready assembled<br>Closing plate |

## Complementary

| | |
|---|---|
| **Main rated current** | 2000 A |
| **Bus rated current** | 1200 A |
| **Enclosure Material** | Painted steel |
| **[Ue] rated operational voltage** | 120/240 V AC |
| **Device mounting** | Surface |
| **Number of Phases** | 1 phase in<br>1 phase out |
| **Service feed location** | UG |
| **Electrical connection** | Lugs 1 AWG 6...300 kcmil aluminium/copper) ground<br>Busbar connection |
| **Wiring configuration** | 3-wire |
| **Height** | 68.90 in (1750.06 mm) |
| **Width** | 30.20 in (767.08 mm) |
| **Depth** | 18.31 in (465.07 mm) |

## Environment

| | |
|---|---|
| **Product Certifications** | UL Listed |
| **Enclosure Rating** | NEMA 3R |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10DE400020 |
| **Discount Schedule** | 0DE4 |
| **GTIN** | 785901671206 |
| **Returnability** | No |
| **Country of origin** | MX |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 68.90 in (175.0 cm) |
| **Package 1 Width** | 30.20 in (76.7 cm) |
| **Package 1 Length** | 18.31 in (46.5 cm) |
| **Package weight(Lbs)** | 342.001 lb(US) (155.129 kg) |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 1317 |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| REACh Regulation | REACh Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |