Product data sheet
Characteristics

PJD36200G
Plug-in unit, I-Line Busway, J-frame, 200A, 3 phase, 3 wire, 600VAC, 14kA, ground

Green Premium™

Main

Range of Product	I-Line
Product or Component Type	Plug-in unit
Module type	J-Frame

Complementary

[Ue] rated operational voltage	600 V AC 50/60 Hz
Phase	3 phase
Busbar description	Ground
Fuse type	J
Breaking capacity code	D
Disconnector device type	Thermal magnetic circuit breaker 200 A 14 kA 600 V Thermal magnetic circuit breaker 200 A 18 kA 480 V Thermal magnetic circuit breaker 200 A 25 kA 240 V
Level or class	Class 5600
Wiring configuration	3-wire

Environment

Product Certifications	CSA[RETURN]UL

Ordering and shipping details

Category	US10PE720185
Discount Schedule	0PE7
GTIN	785901731771
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	32.0001 lb(US) (14.515 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	"WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months