Product data sheet

Specifications

PowerLogic HDPM6000 Expanded Input Module (EIM 2.0), additional digital input module

METSEHDPM6DI

Main

Range	PowerLogic
Product or component type	I/O module
Range compatibility	PowerLogic PowerLogic HDPM6000 base unit

Complementary

Input impedance	47 Ohm
Number of inputs	24 dry contact
Input voltage	5 V DC
Width	157 mm
Depth	58 mm
Height	103 mm

Environment

Ambient air temperature for operation	-20…60 °C
Ambient air temperature for storage	-20…70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.200 cm
Package 1 Width	22.900 cm
Package 1 Length	23.900 cm
Package 1 Weight	1.200 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant with Exemptions**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**