# Product data sheet

Specifications

## Safety switch, heavy duty, non fusible, 400A, 600VAC/VDC, 3 poles, 350HP, NEMA 3R

CHU365R

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Product** | Single Throw Safety Switch |
| **Disconnect Type** | Non-fusible disconnect |
| **Number of Poles** | 3 |
| **Electrical Connection** | Lugs |
| **Duty Rating** | Heavy duty |

## Complementary

| | |
|---|---|
| **Line Rated Current** | 400 A |
| **Factory Installed Neutral** | None |
| **Mounting Type** | Surface |
| **Voltage Rating** | 600 V AC/DC |
| **Standard Motor Power Rating** | 125 hp at 240 V AC 50-60 Hz for 3 phase motors<br>250 hp at 480 V AC 50-60 Hz for 3 phase motors<br>350 hp at 600 V AC 50-60 Hz for 3 phase motors<br>50 hp at 250 V DC<br>50 hp at 600 V DC |
| **Wire Size** | AWG 1/0...750 kcmil copper or aluminium |
| **Tightening torque** | 550 lbf.in (62.1 N.m) (AWG 1/0...750 kcmil) |
| **Height** | 50.31 in (1277.87 mm) |
| **Width** | 27.88 in (708.15 mm) |
| **Depth** | 10.13 in (257.30 mm) |

## Environment

| | |
|---|---|
| **Certifications** | CSA |
| **Enclosure Rating** | NEMA 3R galvannealed steel |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10DE100153 |
| **Discount Schedule** | 0DE1 |
| **GTIN** | 785901181750 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 13.50 in (34.3 cm) |
| **Package 1 Width** | 28.50 in (72.4 cm) |
| **Package 1 Length** | 51.30 in (130.3 cm) |
| **Package weight(Lbs)** | 168.0 lb(US) (76.2 kg) |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 1314 |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| REACh Regulation | REACh Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| Halogen content performance | Halogen free plastic parts product |
| PVC free | Yes |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |