Product data sheet

Specifications

OEM Swbd Interior AL Double-Row Ctr-Fed 1200A 63H 24" Depth

CF12PJ63A

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	I-Line
Product or Component Type	Switchboard interior

Complementary

[Ie] rated operational current	1200 A
bus material	Aluminium
number of rows	2
wire feed	Centre left side
Height	63 in (1600.2 mm)
Width	42 in (1066.8 mm)
Depth	24 in (609.6 mm)
interior maximum breaker frame	250 A right side 1200 A left side
mounting space	2)27 in (685.8 mm) left hand side 1)63 in (1600.2 mm) right hand side

Ordering and shipping details

Category	US1PE1A09484
Discount Schedule	PE1A
GTIN	3606487355960
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	44.02 in (111.8 cm)
Package 1 Width	37.99 in (96.5 cm)
Package 1 Length	65.00 in (165.1 cm)
Package 1 Weight	375.0000000000 lb(US) (170.097 kg)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**

Use Again

Repack and remanufacture

Take-back	**No**