Product data sheet

Specifications

Contactor, Type S, multipole lighting, electrically held, 100A, 3 pole, 220/240VAC 50/60Hz coil, NEMA 1 [TAA]

8903SQG2V03

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	240 V AC 60 Hz 220 V AC 50 Hz
Current Rating	100 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Uden
Other Options	None
Electrical Connection	Lugs
Height	25.2 in (639 mm)
Depth	9.0 in (228 mm)
Width	11.3 in (286 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901625926
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	10.50 in (26.67 cm)
Package 1 Width	12.00 in (30.48 cm)
Package 1 Length	25.50 in (64.77 cm)
Package weight(Lbs)	37.640 lb(US) (17.073 kg)

Contractual warranty

Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained

How we assess product sustainability

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Not compliant**

Use Again

Repack and remanufacture

Take-back	**No**