Product data sheet
Characteristics

QMB321TW
Fuse switch disconnector, QMB Fusible Panelboards, 240VAC, max 30A rating, 3 pole, twin switch unit

Main

Product or Component Type	Fuse-switch disconnector
Number of poles	3
[Ue] rated operational voltage	240 V AC
Line Rated Current	30 A - 30 A 240 V AC
Fuse type	R

Complementary

Number of modules	2
Standards	NEMA KS1
Height	4.49 in (114 mm)

Environment

Product Certifications	CSA[RETURN]UL

Ordering and shipping details

Category	US1PE1A00037
Discount Schedule	PE1A
GTIN	785901748069
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.20 in (13.208 cm)
Package 1 Width	12.60 in (32.004 cm)
Package 1 Length	23.40 in (59.436 cm)
Package 1 Weight	15.94 lb(US) (7.23 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty	18 months