Product data sheet
Characteristics

METSEHDPM125A4
Solid Core Current Transformer HDPM6000, 125 A, 4in lead, for Strip solution

Main

Range	PowerLogic
Product or Component Type	Current transformer
Analogue output type	Voltage output
Electrical connection	Plug-in 4 in (101.60 mm) AWG 18) 600 V
Line Rated Current	125 A

Complementary

Current transformer type	Solid core

Environment

Ambient air temperature for operation	-40…131 °F (-40…55 °C)

Ordering and shipping details

Category	US10PL109795
Discount Schedule	0PL1
GTIN	3606481985415
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.99 in (20.3 cm)
Package 1 Width	7.99 in (20.3 cm)
Package 1 Length	7.99 in (20.3 cm)
Package 1 Weight	10.58 oz (300.0 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.