# Product data sheet

Specifications

## Mini circuit breaker, QO, 20A, 2 pole, 120/240VAC, 10kA, bolt on, aux switch 1A, fungal treatment

QOB2201200FT

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Product** | Miniature circuit-breaker |
| **Range** | QO |
| **Current Rating** | 20 A |
| **Voltage Rating** | 120/240 V AC<br>120 V AC |
| **Mounting Type** | Bolt-on |
| **Number of Poles** | 2P |
| **Circuit Breaker Type** | Standard |
| **Ratings** | HACR rated |
| **Electrical Connection** | Pressure plate |
| **Options** | Auxiliary switch 120 V AC 1A |

## Complementary

| | |
|---|---|
| **Interrupt Rating** | 10 kA 120/240 V AC<br>10 kA 120 V AC |
| **Number of Panel Spaces** | 3 |
| **Wire Size** | AWG 14...AWG 8 copper or aluminium |
| **Tightening Torque** | 35.4 lbf.in (4 N.m) |
| **Height** | 3.0 in (76 mm) |
| **Width** | 1.5 in (38 mm) |
| **Depth** | 2.9 in (74 mm) |
| **Net Weight** | 0.930 lb(US) (0.422 kg) |

## Environment

| | |
|---|---|
| **Certifications** | UL Listed<br>CSA |
| **Ambient Rating** | 104 °F (40 °C) |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10DE200015 |
| **Discount Schedule** | 0DE2 |
| **GTIN** | 00785901085744 |
| **Returnability** | No |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 3.380 in (8.585 cm) |
| **Package 1 Width** | 2.210 in (5.613 cm) |
| **Package 1 Length** | 3.830 in (9.728 cm) |
| **Package weight(Lbs)** | 0.650 lb(US) (0.295 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 18 months |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| SCIP Number | Af42fb01-813d-40c0-ae28-b8b3299dbc99 |
| REACh Regulation | REACh Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| Halogen content performance | Halogen free product |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |

Technical Illustration

**Dimensions**




Dimensions are approximate. Refer to technical documentation for additional detail.