# Product data sheet

Specifications

## Main lugs unit, EZ Meter-Pak, 600A, 120/240VAC, 1ph/3W, 800A bus, OH/UG, Type 3R

EZM1600TB

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | EZ meter-pak |
| **Product or Component Type** | Meter center main unit |
| **Main type** | Main Lugs |
| **Included Items** | Closing plate |

## Complementary

| | |
|---|---|
| **Main rated current** | 600 A |
| **Bus rated current** | 800 A |
| **Enclosure Material** | Painted steel |
| **[Ue] rated operational voltage** | 120/240 V AC |
| **Device mounting** | Surface |
| **Number of Phases** | 1 phase in<br>1 phase out |
| **Service feed location** | OH<br>UG |
| **Electrical connection** | Lugs 1 AWG 6...300 kcmil aluminium/copper) ground<br>Lugs 2 AWG 1/0...750 kcmil aluminium/copper) line<br>Lugs 4 AWG 1/0...300 kcmil aluminium/copper) line<br>Lugs 2 AWG 1/0...750 kcmil aluminium/copper) neutral<br>Lugs 4 AWG 1/0...300 kcmil aluminium/copper) neutral |
| **Wiring configuration** | 3-wire |
| **Height** | 30.46 in (773.68 mm) |
| **Width** | 17.15 in (435.61 mm) |
| **Depth** | 7.09 in (180.09 mm) |

## Environment

| | |
|---|---|
| **Product Certifications** | UL Listed |
| **Enclosure Rating** | NEMA 3R |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10DE400020 |
| **Discount Schedule** | 0DE4 |
| **GTIN** | 785901295976 |
| **Returnability** | Yes |
| **Country of origin** | MX |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 8.000 in (20.320 cm) |
| **Package 1 Width** | 21.000 in (53.340 cm) |
| **Package 1 Length** | 31.300 in (79.502 cm) |
| **Package weight(Lbs)** | 45.309 lb(US) (20.552 kg) |
| **Unit Type of Package 2** | PAL |
| **Number of Units in Package 2** | 10 |
| **Package 2 Height** | 40.000 in (101.600 cm) |
| **Package 2 Width** | 40.000 in (101.600 cm) |
| **Package 2 Length** | 48.000 in (121.920 cm) |
| **Package 2 Weight** | 454.0005 lb(US) (205.931 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 18 months |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 612 |
| Environmental Disclosure | Product Environmental Profile |

### Use Better

#### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| REACh Regulation | REACh Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

### Use Again

#### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |