iq.ul.com

Surge Protective Devices E314042
guide info

Schneider Electric USA, Inc.

Schneider Electric, SURGE PROTECTION BUSINESS, 1751 S 4800 W, Salt Lake City UT 84104

TVS5IMAxx1 (d)

Permanently Connected

SPD Type	Volts (V)	AC/DC DC PV	Phase	Amps (A)	Ambient Min(°C)	Ambient Max(°C)	Mode	VPR (Vpk)	MLV (Vpk)	MCOV (V)	Vn (Vdc)	In (kA)	SCCR (kA)	Notes
1CA	480	AC	3D	N/A	-35	85	L-L	2000	-	550	-	20	200	1
							L-G	1800	-	550	-			

Evaluated to: UL 1449 4th Ed. Rev: 2017-07-21

(d) - Where xx can be 10, 12, 16, 18, 20, 24, 30, 32, 36, or 48,

Note 1 - Suitable for Factory wiring only.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2009-11-10
Last Revised: 2017-10-23

© 2017 UL LLC