Project Name

Location | Prepared By

SATCO S11904

4W/LED/T5/830/BP

Notes

[www] 03-05-2025 00:33:31

General	
Status	Active
Watts	4W
Incandescent Equivalent	25W
Fluorescent Equivalent	8W
Volts	120V-277V
Ballast Type	Type B
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	12
Finish	Frost
CCT (Kelvin)	3000K
Temperature	Warm White
CRI	80+
Lumens	400L
Beam Spread	240
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical	
Ballasting Requirements	No ballast or external driver required
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical	
MOL	11.91
MOD	0.83
Material	Glass
Lens Finish	Frost
Weight (lb.)	0.08

Additional Information	
Additional Info	Replaces F8T5/WW lamps
Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T5 LED Bulbs - Ballast Bypass

Compliance	
Safety Listing	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc.
All Rights Reserved

For More Information Visit:
https://www.satco.com/