HUBBELL
Wiring Device-Kellems

Heavy Duty Products, Insulgrip Pin and Sleeve Devices, Industrial Grade, Male, Plug, 100A 600V AC, 3-Pole 4- Wire Grounding Style 2 and Black

By Hubbell Wiring Device-Kellems
Catalog # HBL4100PS2W

Heavy Duty Products, Insulgrip Pin and Sleeve Devices, Industrial Grade, Male, Plug, 100A 600V AC, 3-Pole 4- Wire Grounding Style 2, Terminal Screws, Gray and Black, Watertight

Application

- Metallic with Nylon Shroud

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 3,000V AC
- Electrical - Max. Working Voltage - 600V AC RMS
- Environmental - Flammability (Enclosure) - UL 94V-0 and CSA C22.2 No. 0.17
- Environmental - Moisture Resistance - Type 3, 4, 4X per UL 50E and CSA 22.2, No. 94
- Environmental - Operating Temperatures - Max. Continuous 75°C
- Min. -40°C w/o impact -25° with impact
- Mechanical - Impact Resistance - Per CSA C22.2, No. 182.1, UL 1682
- Mechanical - Product Identification - Identification and ratings are permanently fastened to the device housing
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 1686(1, 2, 3, Green)

General

Catalog Number	HBL4100PS2W
EU RoHS Indicator	No
Environmental Conditions	Watertight
Item Type	Male Plug
Material	Composite
Material - Mounting Hardware	Cord Mounted
Number Of Poles	3-Pole
Series	UL 1686 Class 1 Insulgrip®
Specifications	• Clamp Nut - Nickel Plated Brass • Gland Cap - Rynite® SST35 • Housing - Valox® 357 • Plug Shroud - Aluminum • Retainer - Thermoset Polyester
Style	Standard Service, Style 2
Type	Watertight Plug
UPC	783585011080

Dimensions

Display Size	Standard Sized

Electrical Ratings

Amperage Rating	100 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	100 A
Current Rating	100 A
Voltage Rating	600 VAC/250 VDC
Voltage Rating Description	600V AC/250V DC

Conductor Related

Cord Type	All Portable
Number Of Wires	4-Wire
Wire Size	#4 AWG to #2 AWG

Certifications And Compliance

Industry Standard(s)	• CSA Certified to CSA Spec. C22.2 No. 159 • UL Listed and CSA Certified Type 4X • UL Standard 1682,UL 50, and UL 1010
Nema Rating	Non-NEMA

Logistics

Carton Quantity	6

Product Assets

Catalogs - WDK Catalog Full 2024
Specifications - HBL4100PS2W
Warranty - Industrial & Commercial Products

©2025 Hubbell Incorporated. All rights reserved