By Burndy
Catalog # K3A2U2

Aluminum Universal Terminal, 3 Conductor, 14-2 AWG (Str)

Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Size	8 AWG;6 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Size Range	14-2 AWG
Number Of Conductors	3
Conductor Size	14-2 AWG
Conductor - Copper Str Size Range	14-2 AWG
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Holes	2
Physical Attribute - Number of Screws	3
Connector Type	Parallel Set-Screw

Dimensions

Dimension - L Length Overall mm	55.62 mm
Dimension - Pad Width inch	1.64 in
Dimension - Height fraction	5/8 in
Dimension - Height inch	0.62 in
Dimension - Height mm	15.7 mm
Dimension - Hole Size fraction	11/32
Dimension - Hole Size inch	0.34 in
Dimension - Hole Size mm	9 mm
Dimension - Stud Size inch	5/16 in
Dimension - Width fraction	1-59/100 in
Dimension - Width inch	1.64 in
Dimension - Width mm	40 mm
Dimension - Bolt Hole Size inch	0.57 in
Dimension - Bolt Size fraction	5/16
Dimension - Length Overall inch	2.19 in
Dimension - D inch	1.63 in
Dimension - N inch	0.34 in

Force Related

Installation Torque Recommended in-lb	50 LBS/in

General

Material - Hardware	Aluminum
Sub Brand	UNIVERSAL TERM
Physical Attribute - Screw Type	Slot
Plated	Y
Type	Bolted Lugs & Terminals
UPC 12 Digit	781810370360
UPC 14 Digit GTIN	00781810370360
Material	Aluminum
Plating Type	Tin plated
UPC	781810370360

Logistics

Minimum Pack Quantity	1
Carton Quantity	216
Pallet Quantity	3240

Operational

Temperature Rating	194

A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved