

| SystemOne Flush Configuration Chart | | | Floor Boxes | | | | | | 4" Core Hole Fire-Rated Poke-Throughs | | |
|--|--|---|---|---|---|---|---|---|---|---|---|
| Approved for use in the City of Chicago. (except S1PFB) | | | Non-Metallic | Metal | | | | | | | |
| Sub-Plates | | | S1PFB | S1CFB | S1SFB | S1SFBCR | S1SFBAV | S1SFBAVCR | S1PTFIT | S1PT4X4FIT | S1PTAVFIT |
| S1SP | Style Line® Decorator/GFCI |  |  |  |  |  |  |  |  |  |  |
| S1SPDU | Duplex/Duplex |  |  |  |  |  |  |  |  |  |  |
| S1SPDUSL | Duplex/Style Line® Decorator |  |  |  |  |  |  |  |  |  |  |
| S1SP4X4 S1SP4X4PA S1SP4X4SYS | Hubbell 4 X 4 Panduit Mini-Com® 4 X 4 SYSTIMAX® 4 X 4 |  |  |  |  |  |  |  |  |  |  |
| S1SP4X4C S1SP4X4PAC S1SP4X4SYSC | Marked with "Ⓢ Controlled" |  |  |  |  |  |  |  |  |  |  |
| S1SPTL | Twist-Lock® Receptacle + Data |  |  |  |  |  |  |  |  |  |  |
| S1SP3IM | Hubbell DataCom + Power |  |  |  |  |  |  |  |  |  |  |
| S1SP4IM | Hubbell DataCom |  |  |  |  |  |  |  |  |  |  |
| S1SPDU2IM | Hubbell DataCom + Duplex |  |  |  |  |  |  |  |  |  |  |
| S1SPSL2IM | Hubbell DataCom + Style Line® Decorator |  |  |  |  |  |  |  |  |  |  |
| S1SPFFxx (Carpet) | Furniture Feed Cover/Flange (Replace "xx" with BRS (Brass finish), AL (Aluminum finish), BL (Black) or GY (Gray). |  |  |  |  |  |  |  |  |  |  |
| S1SPFFTxx (Tile) | |  |  |  |  |  |  |  |  |  |  |
| S1SPEXT1 | Extron® or FSR + Power |  |  |  |  |  |  |  |  |  |  |
| S1SPEXT1C | Marked with "Ⓢ Controlled" |  |  |  |  |  |  |  |  |  |  |
| S1SPEXT2 | Extron® or FSR + Power |  |  |  |  |  |  |  |  |  |  |
| S1SPEXT2C | Marked with "Ⓢ Controlled" |  |  |  |  |  |  |  |  |  |  |
| S1SPEXT3 | Extron® or FSR Single-Service |  |  |  |  |  |  |  |  |  |  |
| S1SPEXT4 | Extron® or FSR + Power |  |  |  |  |  |  |  |  |  |  |
| S1SPEXT4C | Marked with "Ⓢ Controlled" |  |  |  |  |  |  |  |  |  |  |
| S1SPORT | Ortronics Series II® + Power |  |  |  |  |  |  |  |  |  |  |
| S1SPORTC | Marked with "Ⓢ Controlled" |  |  |  |  |  |  |  |  |  |  |
| S1SPTRAC | Ortronics TracJack® + Power |  |  |  |  |  |  |  |  |  |  |
| S1SPTRACC | Marked with "Ⓢ Controlled" |  |  |  |  |  |  |  |  |  |  |
| S1SPMAX | Siemon MAX® + Power | | | | | | | | | | |
| S1SPMAXC | Marked with "Ⓢ Controlled" | | | | | | | | | | |
| S1SPAMM20 | Active Multimedia + Flush Keystone + Power | | | | | | | | | | |
| S1SPAMM20C | Marked with "Ⓢ Controlled" | | | | | | | | | | |
| S1CFCxx (Carpet) | SystemOne Floor Boxes and FRPTs use SystemOne Universal Covers (Replace "xx" with BRS (Brass finish), AL (Aluminum finish), BL (Black) or GY (Gray). | | | | | | | | | | |
| S1TFCxx (Tile) | | | | | | | | | | | |

Signifies minimum depth of concrete pour in inches for Hubbell SystemOne Floor Boxes.

 Recommended Floor Fitting
 Alternative Floor Fitting
 Not Compatible

Extron® is a registered trademark of Extron Electronics. MAX® is a registered trademark of The Siemon Company. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. SYSTIMAX® is a registered trademark of CommScope, Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.