

# Industrial Grade, Locking Switches, General Purpose AC, Momentary Single Pole Double Throw Center Off, 15A 120/277V AC Black Key Guide

By Hubbell Wiring Device-Kellems Catalog # HBL1556L

Switches and Lighting Controls, Industrial Grade, Locking Switches, General Purpose AC, Momentary Single Pole Double Throw Center Off , 15A 120/277V AC, Terminal Screws Black Key Guide

# **Features**

- · Large brass binding head screws with deep slots
- · Lock circuits On or Off
- · Strip gauge for accurate wiring

#### **Application**

Back and Side Wired

### General

Action Color

Contact Configuration Number Of Poles Operating Temperature

Performance

**SPDT** 

- Black
- Noir

Momentary Single Pole

minute

Maximum continuous 75°C and minimum -40°C without Impact

- Electrical Dielectric Voltage - Withstands 1500V AC minimum for 1
- Electrical Max. Continuous Current - 15A
- Electrical Max. Working Voltage - 277V AC
- Electrical Overload -Minimum 4.8 times rated current for 100 cycles
- Electrical Temperature Rise - 30°C maximum at rated current
- Environmental -Flammability - UL 94V-2
- Environmental Operating Temperature - Max. continuous: 75°C, Min. continuous: -40°C without impact
- Mechanical Terminal Accommodations - #14



## **Dimensions**

Dimensions 4.06 in x 1.31 in x 1.89 in

Height 1.89 in
Length 4.06 in
Weight 0.2 lb
Width 1.31 in

#### **Electrical Ratings**

Amperage Rating 15 A

Connectivity Back and Side Wired

Current / Amperage Rating 15 A
Current Rating 15 A

Dielectric Strength Withstands 1500V AC

minimum for 1 minute

Temperature Rise - Max. 30°C maximum at rated

voltage Rating current 120-277 VAC

Voltage Rating Description 120-277 VAC

Conductor Related

Wire Size #14 AWG to #10 AWG

# **Certifications and Compliance**

Industry Standard(s) UL Listed

Logistics

Carton Quantity 10

#### **Product Assets**

Catalogs - WDK Catalog Full 2023 Warranty - Industrial & Commercial Products AWG min. - #10 AWG max. Solid and stranded copper

wire only

Series Extra Heavy Duty

Style Single Pole Double Throw

Type • Locking

Locking

UPC 783585432809



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. WDK\_MX-HBL1556L-SPEC-EN | REV 1/2024