



# 3.5 A, Type Slo-Fast Fuselinks, 23" Length, Removable Head

By CHANCE Utility  
Catalog # [M3D5SFA23](#)

3.5 amp, Type SloFast Cutout fuselink with a 23" (584.2mm) pigtail and a removable buttonhead.



## Features

- Comparable to Cooper/Kearney Type X fuse links
- Compliant with ANSI/IEEE C37.42 - 2016 mechanical interchangeability requirements
- Compatible with universal style expulsion fuse holders
- Dual element design specific for tranformer protection
- Slow portion of time current characteristic curve closely matesches transformers safe loading cureve
- Individually packed for all weather protection
- Type and Current Rating on packaging and fuse for easy identification

## General

Fuse Head Style	Removable
Fuselink Type	Type SloFast
Required Cutout Fuseholder	100 Amp (Do not use in a 200 amp fuseholder.)
Type	Fuselinks
UPC	096359045151

## Dimensions

Length - Fuselink	23" (584.2mm)
Weight	0.098 lb

## Electrical Ratings

Amperage Rating	3.5 A
-----------------	-------

## Logistics

Pallet Quantity	4800
Standard Package	10

## Product Assets

- [Catalogs - Fuse Links \(10B\)](#)
- [Excel Files - Hubbell Time Current Characteristic Curve - Total Clearing Type SloFast](#)
- [Excel Files - Hubbell Time Current Characteristic Curve - Minimum Melt Type SloFast](#)
- [Literature - 38KV 200 KV BIL M3 Disconnenct \(SF11038E\)](#)
- [Literature - SA-M3D\\_C](#)
- [Literature - Switching Line Card\\_FAQ\\_2019](#)
- [Sales Drawings - Fuse Links, Type SF Solid & Removable HD \(PSSASFFUSELINK\)](#)
- [Test Documents - SloFast Min Melt](#)
- [Test Documents - SloFast Total Clear](#)



A proud member of the Hubbell Family.