HUBBELL
Premise Wiring

Fiber LGX Cassette, OM4, SC Duplex to MTP, Aqua

By Hubbell Premise Wiring
Catalog # OCSC50G4

Features

-
-
-

Application

Interconnect

Performance

Optical - Total insertion loss - Less than 1.5dB (test data included)

General

Catalog Number	OCSC50G4
Color	Aqua
EU RoHS Indicator	Yes
Environmental Conditions	Indoor
Item Type	SC Duplex to MTP
Material	Ceramic
Material - Mounting Hardware	Snap-In
Repeatability	0.1 dB
Service Life	500 matings
Style	SC Duplex
Sub Brand	OptiChannel
Temperature Rating	0C to 70C
UPC	662620250847

Dimensions

Display Size	5.1" X 1.1"

Electrical Ratings

Connectivity	Cassette
Insertion Loss	0.75 dB Max
Return Loss	55

Conductor Related

Fiber Size	250 Micron
Fiber Type	OM4

Certifications And Compliance

Industry Standard(s)	• Telcordia GR-326-CORE • TIA-568-C.3 • TIA-604-FOCIS

Logistics

Carton Quantity	25

Product Assets

Brochures - Fiber Connectivity Product Guide
Catalog Page - PREM G06 Catalog Page
Catalog Page - PREM G6 CatalogPage
Catalogs - Premise Wiring Catalog
Sales Drawings - OCSC - PDF
Specifications - PREMISE_OCSC50G4_spec
Specifications - OCSC50G4

©2025 Hubbell Incorporated. All rights reserved