

Flush Round Single or Multi-Service Non-Metallic Floor Boxes, for Use In Concrete Floors

Min. Depth of Pour	3.00" (76.2)
Cubic Inch (cm ³) Capacity	100 cu. in. (1638.7 cm ³) prior to cutting level to floor (19.5 cu. in. (313.2 cm ³) per inch of depth).
Dimensions – A	6.00" (152.4)
Dimensions – B	7.08" (179.8)
Dimensions – C	6.69" (169.9)
Dimensions – D	5.38" (136.5)
Hubs	(2) 1" and (2) 3/4" Conduit Hubs
Concrete Cover Included	✓
Closure/Reducer Plugs	(2) 1" plugs close off 1" hubs or reduce 1" to 3/4" (2) 3/4" plugs close off 3/4" hubs or reduce 3/4" to 1/2"

Description	Catalog Number
Adapter Required for all applications.	PFBA1A
Low Voltage Divider Required for use with catalog number PFB1 when used in multi-service applications. Accepts Hubbell standard duplex receptacles or 15A Twist-Lock® duplex receptacles (HBL4700 series).	PFBT1A
"Y" Adapter 3/4 in. "Y" adapter to feed parallel runs of 3/4 in. conduit.	PFBYA1
Pre-pour PVC stand increases PFB1 box height 2.5 in. to 4.0 in. within the concrete pour.	PFBSTAND

Note: UL File Number E92074. CSA File Number LR18416.

Flush Round Covers and Flanges[†]

Multi-Service Cover and Flange Assemblies
Includes floor box cover with duplex flaps, (2) 1/2 in. dia. low voltage feed through holes and matching carpet flange. 6.25 in. Diameter

SF39253A



Brass

PFBCBRA



Brown Non-Metallic

PFBCBLA



Black Non-Metallic

PFBCGYA



Gray Non-Metallic

PFBCIA



Ivory Non-Metallic

Metal Carpet Flange

Use with single service covers for carpet applications. 6.25 in. Diameter

S3082



Brass

SA3082



Brushed Aluminum

Adapter Ring

Use with single service covers for tile applications.

S5016



Brass

SA5016



Aluminum

Multi-Service Replacement Covers

Material	Metallic	Color	Non-metallic
Solid Brass	BRS2RCA	Black Brown Gray Ivory	PFBRCBLA PFBRCBRA PFBRCGYA PFBRCLA



Single Service Covers[†]

Brass	S3925	S3725	S2525	S2725	S2925	S3525	S3325	S3913
Aluminum	SA3925	SA3725	SA2525	SA2725	SA2925	—	—	SA3913
3.88 in. Dia.								
	Duplex Flap	Duplex Screw	2 1/8" x 3/4" Combination	2 1/8" x 1" Combination	2 1/8" Single Receptacle	2 3/8" Single Receptacle	2 1/8" Single Receptacle (Terrazzo Floor)	Blank

One Piece Brass Cover and Carpet Flange[†]

Brass
Aluminum
6.25 in. Dia.

SF3925*
SFA3925*



Duplex Flap

SFB3926**
SFA3926



Style Line® Decorator Opening

SF2525*



2 1/8" x 3/4" Combination

SF2725*



2 1/8" x 1" Combination

SF2925*




2 1/8" Single Receptacle

Furniture Feed Plate

Unpainted plate with 1 in. threaded opening.

PFBP1



Steel

*Note: Adapter ring S5016 is required for mounting SF series covers onto PFBA1A.

**Note: brass plated aluminum

[†]COVER LOAD RATING; Metallic covers and flanges 2,000 lbs. with 2x safety factor, Non-metallic covers and flanges 300 lbs. Load applied through a 3 in. (76) mandrel at the center of the cover.