Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 7.5kVA

By Acme Electric
Catalog # T2535153S

Low Voltage Distribution Transformer - Single Phase, 240X480 - 120/240V, 7.5kVA

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

ANFC Taps	2
BNFC Taps	2
Catalog Number	T2535153S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	240 X 480
Product Category	Dry Type Distribution Transformer
Secondary Voltage	120/240 V
Taps % Steps	2.5%
UL Insulation Class	180°C
UPC	047503734056
Winding Material	AL
kVA	7.5

Dimensions

Dimensions	10.84 in x 13.5 in x 15.19 in
Height	15.19 in
Length	10.84 in
Weight	115 lb
Width	13.5 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240 X 480 V

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	6

Product Assets

Brochures - General Purpose Dry-Type Distribution Transformers
Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Customer Use Drawings - a-700322
Customer Use Drawings - a-125881
Customer Use Drawings - a-125852
Customer Use Drawings - a-125877
Customer Use Drawings - a-125893
Customer Use Drawings - a-125883
Customer Use Drawings - a-125873
Customer Use Drawings - a-102722-b
Customer Use Drawings - a-125885
Engineering Drawing - T2535153S
SDS - HCC SDS
Specifications - T2535153S
Terms and Conditions - HCC Terms & Conditions

©2025 Hubbell Incorporated. All rights reserved