HUBBELL
Premise Wiring

Non-Metallic Raceway, PolyTrak Series, PolyTrak Box, 1-Gang, 1.78" Depth Standard

By Hubbell Premise Wiring
Catalog # PDB12S

Non-Metallic Raceway, PolyTrak Series, PolyTrak Box, 1-Gang, 1.78" Depth Standard

Performance

- Environmental - Flame Rating - UL94V-0
- Environmental - Temperature Range - -25.6° to 158° F

General

Catalog Number	PDB12S
Color	Office White
EU RoHS Indicator	Contact Manufacturer
Item Type	PW2 WallTrak, PL1 LANTrak and PP1 PremiseTrak (Latching) Series
Number of Gang(s)	1-Gang
Series	• PP1 • PL1 • PW2
Specifications	• Crush Resistance - 300 lbs. • Impact Resistance - 5 ft. lbs. • Material - UV Stabilized PVC • Style - 1-Gang
Style	Standard
Type	Boxes
UPC	783585090405

Certifications And Compliance

Industry Standard(s)	• CSA Standard C22.2 no. 62 • E118895 / E119190 • UL Standard UL 5A

Logistics

Carton Quantity	5
Pallet Quantity	1040

Product Assets

Catalog Page - PREM U57 Catalog Page
Catalog Page - WDK S-62 Catalog Page
Catalog Page - PREM U56 Catalog Page
Catalog Page - WDK S-58 Catalog Page
Catalog Page - WDK S-56 Catalog Page
Catalog Page - WDK S-55 Catalog Page
Catalog Page - PREM U59 Catalog Page
Catalog Page - PREM U63 Catalog Page
Catalogs - WDK Catalog Full 2024
Catalogs - Premise Wiring Catalog
Specifications - PDB12S

©2025 Hubbell Incorporated. All rights reserved