

# GAR1829, Mechanical Grounding Connector, Cable to Rod or Pipe

By Burndy Catalog # GAR1829

Mechanical Grounding Connector, Cable to Rod or Pipe, 2/O AWG (Sol) -250 kcmil, 2" Pipe, 2"-2-3/8"Rod, Bright Dipped.



### **Application**

For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Direct Burial Cable, Fence Post

#### General

EU RoHS Indicator Yes
Installation Torque 240 Lb-in

Recommended Run in-lb

Installation Torque 240 LBS/in

Recommended in-lb

Material Copper

Material - Hardware DURIUM™ Silicon Bronze

Plated

Plating Type Bright Dipped

Sub Brand MECHANICAL CONNECTOR

Type GAR U Bolt Type 310

UPC 781810235201 UPC 12 Digit 7818102352011

#### **Dimensions**

Dimension - B Length inch 2.75 in Dimension - Height fraction 4-1/2 in Dimension - Height inch 4.50 in Dimension - L Length Overall 46 mm 1.81 in Dimension - Length Overall Dimension - Outside Diameter 2.38 in Dimension - Width fraction 3-3/4 in Dimension - Width inch 3.69 in Dimension - Width mm 94 mm

#### **Conductor Related**

Conductor - Copper Solid Size 2/0 AWG

Conductor - Copper Solid Size 2/0 AWG-4/0 AWG

Range

Conductor - Copper Str Size 250 Kcmil
Conductor - Copper Str Size 1/0 -250 kcmil

Range

Conductor - Copper Tube Std 2 IPS IPS

Size

Conductor - Copper Tube Std 2 IPS IPS

Size Range

Conductor - Pipe or Round 2 in

Tube Size Range

Conductor - Rod Size 2 i

Conductor - Rod Size Range

Conductor Type

2 in-2.38 in

2 in-2 3/8 in

CU C Solid-Size

• CU C Str-Size

• CU Tube Std-Size

Rod-Size

#### **Certifications and Compliance**

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
UL Listed	Yes

## **Product Assets**

3D Models - GAR1829\_MODEL-IGES 3D Models - GAR1829\_MODEL-PDF 3D Models - GAR1829\_MODEL-STEP Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SD..015789-01

