

## New Innovations

### Circuit-Lock® 30A Disconnects with LED Indicators

Hubbell's new 30A Circuit-Lock Disconnect with integral phase indication LEDs redefines the benchmark for safety by providing insight into the enclosure while in use. Six highly visible LEDs (3 line side/3 load side) communicate the electrical status of the switch by phase. This voltage detection feature significantly improves existing safety and maintenance procedures by visually providing personnel critical information prior to removing the enclosure cover; e.g. a welded contact or dropped phase.

Hubbell **inSIGHT™** phase indicating disconnect switches are available in non-metallic and stainless steel versions. Replacement covers are available for upgrades to existing installations. With an ever growing focus on safety improvements Hubbell **inSIGHT™** disconnects provide a difference you literally can see.

# inSIGHT™

*Insight (n): the power or act of seeing into a situation*



#### Housing Design

- Six highly visible integral phase identification LEDs provide secondary means of visual confirmation of make/break on all phases
- Available in non-metallic, stainless steel and jog switch versions
- IP69k and Type 4X, 12K water ingress protection



#### Safety

- High visibility red handle can be locked in the OFF position to comply with OSHA Lockout/Tagout requirements
- Quickly upgrade the safety of existing installations with an **inSIGHT™** replacement cover
- Verification of opening of load side contacts



### Unfused Disconnect Switches with LEDs

Description	30 Amp	60 Amp	100 Amp
Non-Metallic disconnect switch with LEDs	<b>HBLDS3P</b>	<b>HBLDS6P</b>	<b>HBLDS10P</b>
Non-Metallic disconnect switch with HBLAC1 auxiliary contact	<b>HBLDS3PAC</b>	<b>HBLDS6PAC</b>	<b>HBLDS10PAC</b>
Non-Metallic disconnect switch with HBLAC2 auxiliary for use with VFDs	<b>HBLDS3PVFD</b>	—	—
Stainless Steel square top disconnect switch with LEDs	<b>HBLDS3SSP</b>	<b>HBLDS6SSP</b>	<b>HBLDS10SSP</b>
Stainless Steel square top disconnect switch with HBLAC1 auxiliary contact	—	<b>HBLDS6SSPAC</b>	<b>HBLDS10SSPAC</b>
Stainless Steel sloped top disconnect switch with LEDs	<b>HBLDS3SSRP</b>	<b>HBLDS6SSRP</b>	<b>HBLDS10SSRP</b>
Stainless Steel sloped top disconnect switch with HBLAC1 auxiliary contact	—	<b>HBLDS6SSRPAC</b>	<b>HBLDS10SSRPAC</b>

Note: \*Certified by NSF, International.  
For use with 3Ø Y configurations only.

### Auxiliary Contacts

Description	Catalog Number
"Break After Main Break", 1 set of n/o contacts, 1 set of n/c contacts.	<b>HBLAC1**</b>
"Break Before Main Break", 1 set of n/o contacts for use with variable frequency drives.	<b>HBLAC2**</b>



HBLDS3P



HBLDS3SSRP