



MF TYPE CURVED LOCK NUT, 1/2in THREAD

By CHANCE Utility
Catalog # [3511](#)

Used with regular square nuts to create a vibration resistant fit. When the MF lock nut contacts the regular nut, turn an additional 1/2 to 3/4's turn with wrench to firmly lock in place.



*Representative Image

Features

- For 1/2" diameter bolt, tapped 1/2-13-UNC
- Hot dip galvanized per ASTM A-153
- RUS listed, ek - Locknut.

General

Coating	Galvanized, ASTM A-153
Material	Steel
UPC	096359070214

Dimensions

Distance From Pole	N/A
Weight	0.03 lb

Certifications and Compliance

RUS Listed Reference	ek - Locknut
----------------------	--------------

Logistics

Pallet Quantity	48000
-----------------	-------

Product Assets

[Catalogs - Communications Catalog \(CA12042E\)](#)
[Catalogs - Pole Line Hardware](#)
[Sales Drawings - MF Lockout \(SA3510\)](#)

Related Products

[8710 - BOLT, MACHINE, SQ HEAD, 1/2in x 10in](#)
[8645 - BOLT, CARRIAGE, SQ NECK, 1/2in x 5in](#)
[6811 - WASHER, SQ FLAT, 9/16in HOLE, 2in SQ](#)
[PS6802 - WASHER, ROUND, 9/16in HOLE, 1-1/4in DIA.](#)



A proud member of the Hubbell Family.