

YCB25R

By Burndy
Catalog # [YCB25R](#)



Permanent compression hot-line clamp adapter with aluminum run and copper bail. Permits hot-line tapping without arcing or chafing damage to aluminum conductor, Aluminum:1/0 (7, 19).

Application

For Aluminum, ACSR, 6201, 5005, Compressed And Compact Conductors

General

Die Index	C
EU RoHS Indicator	Yes
Material	Aluminum
Material - Bail	Copper
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Sub Brand	CRIMPIT
Type	Stirrups
UPC	781810151716
UPC 12 Digit	7818101517166

Dimensions

Dimension - Bail Size	2
Dimension - D inch	2.50 in
Dimension - F Width Center to Center inch	3.50 in
Dimension - Height inch	4.91 in
Dimension - L Length Overall mm	246 mm
Dimension - Length Overall inch	9.69 in

Conductor Related

Conductor - ACSR Str Size	1/0 (6/1) Raven AWG;2/0 (6/1) Quail AWG;3/0 (6/1) Pigeon AWG;4/0 (6/1) Penquin AWG;80 (8/1) Grouse kcmil
Conductor - ACSR Str Size Range	1/0 (6/1) Raven AWG-80 (8/1) Grouse kcmil
Conductor - AL Str Size	1/0 AWG
Conductor - AL Str Size Range	1/0 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[3D Models - YCB25R_MODEL-STEP](#)
[3D Models - YCB25R_MODEL-IGES](#)
[3D Models - YCB25R_MODEL-PDF](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - SD..029790-01](#)