KILLARK®

OLR-5 - 1-1/2″ LR Hub, Aluminum O Series Conduit Body

By Killark
Catalog # OLR-5

1-1/2″ LR Hub, Aluminum O Series Conduit Body

*Representative Image

Features

- Raintight when used with gasketed covers.
- Malleable iron suitable for use in concrete.
- Interchangeable with competitive products.
- Stainless steel screws on stamped and cast covers.
- Tapered threaded hubs (NPT).

Application

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

General

Catalog Number	OLR-5
Color	Gray
EU RoHS Indicator	Contact Manufacturer
Finish Type	Powder Epoxy Paint
Hub Pattern	LR
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	O Series
Type	Conduit Body
UPC	783936490557

Dimensions

Dimensions	10.25 in x 5 in x 3.125 in
Gross Weight with Packaging	1.41
Height	3.125 in
Hub Size	1-1/2″
Length	10.25 in
Width	5 in

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2025)
CSA File Number	LR11852
Hazardous Rating(s)	Suitable for use in hazardous location applications when installed according to NEC Articles 501.10(b) (Class I, Division 2) or 502.10, 503.10, and 505.15 (Class I Zone 2).
UL File Number	E3397

Product Assets

3D Models - OLR-5 3D Model
Catalogs - Killark Catalog
Certifications - E Series, O Series, CO & TW Series Conduit Bodies CSA Certificate of Conformity
Customer Notices - Prop 65 Notice
Engineering Drawing - OLR-5 Engineering Drawing
Sales Drawings - OLR-5 Sales Drawing
Specifications - O Series & Form 5 Cross Reference
Specifications - Conduit Fill Information
Specifications - O Series & Duraloy 5 Series Conduit Bodies Specification Sheet

©2025 Hubbell Incorporated. All rights reserved