



Anchor, PISA Rod, 5/8in X 7ft Thimbleye, 5/8in threads

By CHANCE Utility
Catalog # [E1020035](#)

Pisa anchor rod 0.625" (15.9 mm) diameter, 7' (2134 mm) long with Thimbleye.



*Representative Image

Features

- Hot forged hex collar provides strong connection to anchor and eye
- Hot dipped galvanized per ASTM A153
- Eye nut assembled to rod
- Rods used with PISA® Power Installed Screw Anchors
- Cannot be used with Expanding and Plate Anchors

Application

Helical Anchoring

General

Coating	Galvanized, ASTM A-153
Eye nut Style	Thimbleye
Strength Note	Ultimate strength ratings apply to properly installed anchors only. Failure to install within 5 ° of alignment with the guy load may significantly lower strength.
Tensile Strength	16000 lb
Type	Power Installed Screw Anchor (PISA)
UPC	096359076827

Dimensions

Length	84.000 in
Rod Diameter	0.625 in
Weight	7.840 lb

Logistics

Pallet Quantity	50
Standard Package	5

Product Assets

- [Catalogs - Anchors \(4\)](#)
- [Installation Manuals - TD06131E_PISA_Anchors](#)
- [Literature - CHANCE Anchor Tool Inspection and Maintenance \(TD06031E\)](#)
- [Literature - Anchoring \(CA12002E\)](#)
- [Sales Drawings - Pisa-Rod Eye nut- Combination \(SA1020031\)](#)
- [SDS - MSDS - Galvanized Steel Products](#)
- [Video - CHANCE Tough One and PISA Anchor Installation \(VI0645E\)](#)
- [Video - CHANCE Pisa Drive Tools \(VI0633E\)](#)

Related Products

- [12587 - Anchor, PISA Nut, 5/8in threads, Thimbleye](#)
- [12332P - Anchor, PISA Rod, 5/8in X 7ft, 5/8in threads](#)
- [G5067 - Thimbleye® ANCHOR ROD BONDING CLAMP for 5/8in PISA RODS](#)



A proud member of the Hubbell Family.