BIBD2506FX, Double Sided Flex Rated Six Conductor Clear Insulated Mult-Tap Connector

By Burndy
Catalog # BIBD2506FX

Aluminum UNITAP, Double Sided Entry, #10-250 Class B & C ,#10-3/0 Class G,H,I,K, DLO, 6 PORT.

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory
- Suitable for Code and Flex Conductor
- Color-coordinated conductor port caps display wire range and classes of conductor accepted
- Screw port caps show installation torque information for easy reference

General

Catalog Number	BIBD2506FX
Connector Type	Multi Tap
Insulation	Y
Material	Aluminum
Plated	Y
Plating Type	Tin
Temperature Rating	-40° C to 135 °C
Trade Name	UNITAP™
UPC	621945439122
UPC 14 Digit GTIN	00621945439122

Dimensions

Dimension - Height mm	0 mm
Dimension - Length Overall inch	5.532 in

Electrical Ratings

Amperage Rating	255 A
Voltage - Maximum	600 V

Conductor Related

Conductor - AL Str Size Range	10 AWG - 3/0 AWG
Conductor Size	10 AWG-250 KCMIL
Conductor Type	• AL C Str-Size • CU C Str-Size

Certifications And Compliance

Certification - CSA Approved	Yes
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	1

Product Assets

Catalogs - UNITAP™ Products
Catalogs - BURNDY Master Catalog - Section A - Mechanical
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Sales Drawings - 50046931
Specifications - BIBD2506FX

©2025 Hubbell Incorporated. All rights reserved