HUBBELL
Wiring Device-Kellems

Locking Devices, Twist-Lock®, Marine Grade, Flush Receptacle, 30A 125V, 2-Pole 3-Wire Grounding, L5-30R, Screw Terminal, Yellow

By Hubbell Wiring Device-Kellems
Catalog # HBL26CM10

Locking Devices, Twist-Lock®, Marine Grade, Corrosion Resistant Single Flush Receptacle, 30A 125V AC, 2-Pole 3-Wire Grounding, NEMA L5-30R, Screw Terminal, Nylon face, Yellow.

Features

- Wire restraint recess for both back and side wiring, greatly reduces the possibility of loosening the terminal connection
- Face color coding by voltage facilitates locating and mating of proper devices
- Nickel plated brass mounting and grounding system provides a lower resistance ground path and greater resistance to corrosion than steel mounting systems

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17
- Environmental - Moisture Resistance - IP20 Suitability
- Environmental - Operating Temperatures - Maximum Continuous 75°C Minimum -40°C (w/o impact)
- Mechanical - Terminal Accommodation - #16 AWG - #8 AWG stranded copper wire only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

General

Catalog Number	HBL26CM10
EU RoHS Indicator	Yes
Environmental Conditions	Corrosion Resistant
Horsepower - Maximum	2
Item Type	Single Flush Receptacles
Material	Nylon
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Specifications	• Base - Glass-Reinforced thermoplastic polyester (RTP) • Contacts - Nickel Plated Brass • Face - Nylon • Mounting Strap - Nickel Plated Brass • Terminal Screws - #10 - 32 Bronze
Type	Single Flush Receptacle
UPC	783585808192

Dimensions

Dimensions	3.28 in x 1.70 in x 1.31 in
Display Size	Standard Sized Product
Height	1.31 in
Length	3.28 in
Weight	0.3 lb
Width	1.7 in

Electrical Ratings

Amperage Rating	30 A
Connectivity	Back and Side Wired Screw Terminals
Current / Amperage Rating	30 A
Current Rating	30 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 VAC

Conductor Related

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Industry Standard(s)	• Listed to UL 498 • Fed.Spec. W-C-596

	• Certified to CSA C22.2 No.42 • WR Rating
Nema Rating	L5-30R
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	10
Pallet Quantity	840

Product Assets

Catalog Page - WDK B-29 Catalog Page
Catalog Page - WDK AA-11 Catalog Page
Catalog Page - WDK AA-5 Catalog Page
Catalog Page - WDK N-18 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - HBL26CM10 AutoCAD Drawing
Installation Manuals - WIRING_PD1555_INSTALLINST
Literature - Hubbell Marine Full Line Catalog
Sales Drawings - WDK_HBL26CM10_DRAWING_PDF
Specifications - Wiring HBL26CM10 Specification Sheet
Warranty - Industrial & Commercial Products
Video - Insulgrip Twist-Lock and Straight Blade Devices
Video - Marine Electrical Products
Video - Twist-Lock Devices

A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved