




For Use in Raised Access or Wood Floors

Inches (mm)

AFB series boxes are available from our factory as pre-wired assemblies with CONNEXION modular plug-n-play system

Style



Box Type

| Standard Chicago (No Knockouts) | AFB4G50 AFB4G50CHI | AFB4G25 AFB4G25CHI |
|---|-------------------------------------|--|
| Minimum Depth from Top of Floor Tile | 5.37" (136.4) | 2.88" (73.2) |
| Cubic Inch (cm ³) Capacity per Gang | 57.5 cu. in. (940 cm ³) | 26.5 cu. in. (434.3 cm ³) |
| Dimensions – A | 5.18" (131.4) | 2.69" (68.3) |
| Dimensions – B | 11.11" (282.2) | 11.11" (282.2) |
| Dimensions – C | 10.90" (276.9) | 10.90" (276.9) |
| KO Trade Size: | Ends Sides Bottom | (2) 1/2", (4) 1", 1 1/4", 1 1/2", 2" (4) 1/2", 3/4", 1", 1 1/4" (4) 1/2", 3/4", 1", 1 1/4" |
| Cover Family | Rectangular | Rectangular |
| Temporary Cover Included | ✓ | ✓ |

Rectangular Covers (For use with raised access tile and wood floors)

- Die cast construction available in five finishes
- UL 514A listed
- Maximum static load of 1500lb with 2x safety factor*

Cover Dimensions 13" x 13 1/4"



| Finish | Flush Surface | With Insert |
|--------------------------|--------------------|---------------------|
| Aluminum Powder Coat | 4GAFBCVRALU | 4GAFBCVRALUC |
| Black Powder Coat | 4GAFBCVRBK | 4GAFBCVRBKC |
| Brass Powder Coat | 4GAFBCVRBRS | 4GAFBCVRBRSC |
| Bronze Powder Coat | 4GAFBCVRBRZ | 4GAFBCVRBRZC |
| Satin Nickel Powder Coat | 4GAFBCVRNK | 4GAFBCVRNKC |

*Load applied through a 3" (76mm) mandrel in center of the cover

Plates for Use in 2, 4 and 6-Gang Floor Boxes

UL 514A listed

| Plate Style | (1) Decorator Opening | (1) Duplex Opening | (2) Extron® MAAP Openings | (2) Extron® Openings | (2) 1U Hubbell iSTATION Openings | (1) 1.5U Hubbell iSTATION Opening | (1) Simplex Opening 1.40" Diameter |
|-------------|--|--------------------|---------------------------------|---|--|--|------------------------------------|
| Cat. No. | FBMPREC | FBMPDUP | FBMPMAAP | FBMPAAP | FBMP2IM | FBMP15IM | FBMP139 |
| Image | | | | | | | |
| Plate Style | (1) Twist-Lock® Opening 1.60" Diameter | 1-Gang Blank | Cable Feed Through with Bushing | (1) Opening for TracJack® or Series II® | (2) Hubbell Jack Openings and (4) Jack KOs w/Label Field | (1) Opening with Hubbell ISF6 Frame for Keystone Jacks | |
| Cat. No. | FBMP156 | FBMPBNK | FBMPFT | FBMPTRAC | FBMP6DJ | FBMP6KS | |
| Image | | | | | | | |

Extron is a registered trademark of Extron Electronics. Crestron is a registered trademark of Crestron Electronics, Inc. FSR is a registered trademark of FSR Inc. TracJack, Series II and Ortronics are registered trademarks of Ortronics/Legrand.

ScrubShield®
Complies with UL514 A