YSH3429 Compression H-Tap Connector

By Burndy
Catalog # YSH3429

Copper Compression Double H - Tap Connector, 1/0 AWG - 250 kcmil (Tap 1), 1-6 AWG (Tap 2), 8-14 AWG (Tap 3), 4/0 AWG - 500 kcmil (Run).

Features

- Accommodates a wide range of Run/Tap Copper cable combinations including both flexible and code combinations allowing maximum flexibility
- Tap grooves function independently from each other, use of one tap is required, balance may be used or left empty

Application

For High Voltage (15 KV) Power Cables With Copper Conductors

General

Catalog Number	YSH3429
Color Code	Brown
Connector Type	H-Tap
Die Index	1104
EU RoHS Indicator	Yes
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	CRIMPIT
Trade Name	CRIMPIT™
Type	Taps
UPC	781810038406
UPC 14 Digit GTIN	00781810038406

Dimensions

Dimension - Height inch	2.23 in
Dimension - Height mm	56.6 mm
Dimension - Length Overall inch	3.00 in
Dimension - Strip Length inch	1 1/2
Dimension - Width inch	1.31 in
Dimension - Width mm	33 mm

Conductor Related

Conductor - Copper Flex G Run	4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Flex G Run Range	4/0 AWG-500 kcmil
Conductor - Copper Flex G Tap	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Flex G Tap Range	1/0 AWG-250 kcmil
Conductor - Copper Flex H Run	4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Flex H Run Range	4/0 AWG-500 kcmil
Conductor - Copper Flex H Tap	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Flex H Tap Range	1/0 AWG-250 kcmil
Conductor - Copper Str Run	4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Str Run Range	4/0 AWG-500 kcmil
Conductor - Copper Str Tap	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Tap Range	1/0 -250 kcmil

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	20
Minimum Pack Quantity	1
Pallet Quantity	1920

Product Assets

Catalogs - BURNDY Master Catalog - Section C - Compression Connections
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_YSH_LineArt
Sales Drawings - 20880601
Specifications - YSH3429

A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved