



MF TYPE CURVED LOCK NUT, 3/8in THREAD

By CHANCE Utility
Catalog # [3510](#)

Used with regular square nuts to create a vibration resistant fit. When the MF lock nut contacts the regular nut, turn an additional 1/2 to 3/4's turn with wrench to firmly lock in place.



*Representative Image

Features

- For 3/8" diameter bolt, tapped 3/8-16-UNC
- Hot dip galvanized per ASTM A-153
- RUS listed, ek - Locknut.

General

Coating	Galvanized, ASTM A-153
Material	Steel
UPC	096359070207

Dimensions

Distance From Pole	N/A
Weight	0.01 lb

Certifications and Compliance

RUS Listed Reference ek - Locknut

Product Assets

[Catalogs - Communications Catalog \(CA12042E\)](#)
[Catalogs - Pole Line Hardware](#)
[Sales Drawings - MF Lockout \(SA3510\)](#)

Related Products

[8636 - CARRIAGE BOLT, 3/8in x 6in, 4,250 RATED TENSILE STRENGTH](#)
[8604 - BOLT, MACHINE, SQ HEAD, 3/8in x 4in](#)
[PS6801 - WASHER, ROUND, 7/16in HOLE, 1in DIA.](#)
[C2050188 - SPRING WASHER, REGULAR-DUTY DOUBLE-COIL, 3/8in SIZE](#)



A proud member of the Hubbell Family.