lumbergautomation
A BELDEN BRAND

Product: RKHS 8X-RJ45 G-478

Gigabit Ethernet Cat7 data double-ended cord set, M12 X-code female receptacle to male straight RJ45, shielded, black PUR, 8-wires, 4x2x0.14 mm²

Product Description

Gigabit Ethernet Cat7 data double-ended cord set, M12 X-code female receptacle to male straight RJ45, shielded, black PUR, 8-wires, 4x2x0.14 mm²

Technical Drawing







Technical Specifications

Face View Side 1

Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8
white	orange	white	green	white	brown	white	blue

Face View Side 2

Pin 1	Pin 2	Pin 3	Pin 4	Pin 5	Pin 6	Pin 7	Pin 8
white	orange	white	blue	white	green	white	brown

Product Description

Brand:	Lumberg Automation
Connector Type:	Cordset, double ended
Shielding Type:	Shielded
Voltage Rating:	60 V
Rated Impulse Voltage:	0.8 kV
Current Rating:	0.5 A
Data Transmission Type:	Gigabit Ethernet Cat7
Data Transmission Rate:	10 Gbit/s

Technical Data Side 1

Side 1 Product Sub Family:	M12 Overmolded Receptacle
Connector Design:	Straight
Attachment Type:	Coupling nut
Number of Pins:	8
Coding, Side 1:	X
Contact Resistance:	≤ 10 mOhm
Insulation Resistance:	> 10^9 Ohm
Mating Cycles:	≤ 100
Ambient Temperature (Operation)*:	- 40 °C - + 70 °C
Protection Degree / IP Rating**:	IP65, IP67
Design Standard:	IEC 61076-2-109
Pollution Degree:	3 acc. to DIN EN 60664-1 (VDE 0110-1)
Contact Base Material:	CuZn
Side 1 Contact Plating:	Cu/Au
Contact Bearer Material:	PA
Contact Bearer Color:	Black
Flammability Class (Contact Bearer):	UL 94 V-0
Molded Body Material:	TPU
Molded Body Color:	Black
Attachment Material:	CuZn
Attachment Plating:	Nickel-plated
Shielding Material:	GD-Zn, nickel-plated
Fastening Torque (Attachment):	M 12x1: (50-60) Ncm, hand-tight

Cable Data

Cable Number:	478
Conductor Size:	4x2x0.14 mm²
Number of Wires:	8
Conductor Material:	Cu
Cable Jacket Material:	PUR
Cable Jacket Color:	Black
Cable Diameter D:	ø 6.8 ± 0.3 mm
Insulated Wire Diameter:	ø 1.05 ± 0.05 mm
Overall Shield (Cable):	Cu-ETP1 tinned
Ambient Temperature (Fixed Installation):	- 40 °C - + 70 °C
Ambient Temperature (Flex Installation):	0 °C - +50 °C
Flammability Class (Cable Jacket):	IEC 60332-1-2
Core Colors:	Twisted pairs: white & blue, white & orange, white & green, white & brown

Technical Data Side 2

Side 2 Product Sub Family:	RJ45
Connector Design, Side 2:	Straight
Attachment Type, Side 2:	RJ45
Number of Pins, Side 2:	8
Contact Resistance, Side 2:	≤ 20 mOhm

Insulation Resistance, Side 2:	> 10^9 Ohm
Mating Cycles, Side 2:	≤ 750
Ambient Temperature (Operation), Side 2*:	- 40 °C - + 70 °C
Protection Degree / IP Rating, Side 2**:	IP20
Design Standard, Side 2:	IEC 60603-7
Pollution Degree, Side 2:	3 acc. to DIN EN 60664-1 (VDE 0110-1)
Overvoltage Category, Side 2:	I acc. to DIN EN 60664-1 (VDE 0110-1)
Contact Plating, Side 2:	Cu/Au
Contact Bearer Material, Side 2:	PC
Contact Bearer Color, Side 2:	Clear
Molded Body Material, Side 2:	TPE
Molded Body Color, Side 2:	Black
Attachment Material, Side 2:	CuZn
Attachment Plating, Side 2:	Nickel-plated
Shielding Material, Side 2:	CuZn, tin-plated

Safety & Environmental Compliance

RoHS Compliant:	yes

Resistances

Rail:	No
Oil Resistance:	IEC 60811-2-1

Notes

Note Derating:	Notice derating

History

Update and Revision:	Revision Number: 0.16 Revision Date: 07-17-2025

Variants

Item #	Item Description	Cable Length
14750	RKHS 8X-RJ45 G-478/0,5 M	0.5 m
27396	RKHS 8X-RJ45 G-478/0,6 M	0.6 m
14749	RKHS 8X-RJ45 G-478/1 M	1 m
14747	RKHS 8X-RJ45 G-478/2 M	2 m
9X0023931	RKHS 8X-RJ45 G-478/3 M	3 m
23930	RKHS 8X-RJ45 G-478/5 M	5 m

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.