TINGLEY

est. 1896

Safetyflex® Jacket

Stock Number - J41008

Compliance Standards: Flame resistant. Self extinguishing with flameout and afterglow less than or equal to 2 seconds after removal of ignition source and char length of less than 6 inches. Test Method ASTM D6413.

Garment Detail:

The jacket has tapered raglan sleeve construction with a 90 degree sleeve-to-body angle, a storm fly front with hidden snap closure, and an inner storm flap. The oversized collar has an extended throat guard with 'hook and loop' closure tabs.

Garment Type: High performance rainwear, provides superior protection against acids, caustics, and chemicals.

Sizes: M, L, XL, 2X, 3X, 4X

Color: Green

Material: Green material is 13 oz./yd² Specialty PVC on 150D Polyester.

Seam Construction: All seams are RF/heat sealed and 100% waterproof.

Closure Type: Hidden snap closure with 4 snaps and storm fly.

Pockets:

Labels/Tags:

Label sealed to inside collar displays Tingley logo, size, Flame Resistance and country of origin. Care instructions, fabric composition, lot and date codes are located on the reverse.

Packaging: Printed polyethylene bag.

Other: Mildew Resistant.

Dimensions	M	L	XL	2X	3X	4X
Chest	50"	54"	58"	62"	66"	70"
Length	30"	31"	31"	32"	32"	32"
Sleeve Length	34"	34.5"	35"	35.5"	36"	36"

Case Pack: 12 each

Case Dimensions/Weight

M = 15"(L) X 13"(W) X 10"(H) / 19 lbs.	2X = 15"(L) X 13"(W) X 10"(H) / 23 lbs.
L = 15"(L) X 13"(W) X 10"(H) / 20 lbs.	3X = 15"(L) X 13"(W) X 10"(H) / 25 lbs.
XL = 15"(L) X 13"(W) X 10"(H) / 22 lbs.	4X = 15"(L) X 13"(W) X 10"(H) / 26 lbs.

Safetyflex® is a registered trademark of Tingley Rubber Corp.