We connect and protect

Rebar Grounding Clamp, Perpendicular

CATALOG NUMBER

EK17

CERTIFICATIONS

FEATURES

- Universal use for rebar, rods or pipes
- Lay-in feature cuts installation time
- Bronze alloy construction with Stainless Steel 304 screws
- Approved for direct burial in earth and concrete

PRODUCT ATTRIBUTES

- Material: Bronze;Stainless Steel 304 (EN 1.4301)
- Connection Type: Perpendicular
- Conductor Size: #10 Solid - #2 Solid;5.5 mm² Stranded - 25 mm² Stranded
- Ground Rod Diameter, Actual (Ø): 0.5" - 1"
- Water Pipe Size (Ø): 1/2" - 1"
- Rebar Size, US: #4 – #8
- Rebar Size, Canada: 10M – 25M

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.