PIPE SUPPORT SYSTEM:

APPLICATION:

- Effectively anchors and supports lightweight CSST, as well as other fuel gas piping materials to any roofing membrane.

MATERIAL / SPECIFICATIONS:

- Made of 100% recycled material, UV resistant and waterproof.
- Will not damage expensive roof membranes.
- Installs on any roof with or without standard roof adhesives.

Pipe Supports

PIPE SUPPORT SYSTEM

Part No.	Description	Pkg. Qty.	Lbs./Ea.
RB0-10-4	Rubber Support Block (10"L x 4"H)	1 Ea.	4.9
RB1-10-5	Rubber Support Block w/ ⅞" Galv Steel Channel (10"L X 5"H)	1 Ea.	6
RB1-29-5	Rubber Support Block w/ ⅞" Galv Steel Channel (29"L X 5"H)	1 Ea.	18
RB2-10-12	Rubber Support Block w/Adj height ⅞" Galv Steel Channel (10"L x 5"-12"H)	1 Ea.	7.7

MULTI-PORT MANIFOLDS:

APPLICATION:

- Provides central distribution point for individual runs to each appliance.

MATERIAL / SPECIFICATIONS:

- Cast 3, 4, and 5 Port – ASTM A536-84 Ductile Iron.

Cast Manifolds

MULTI-PORT MANIFOLDS

Part No.	Description	Pkg. Qty.	Lbs.
3-PORTMAN	Cast 3 port – ¾"F x 3 @ ½"F x ½"F	1 Ea.	1.5
3-PORTMAN-1	Cast 3 port – ½" x 3 @ ½"F x ½"F	1 Ea.	1.5
4-PORTMAN-10	Cast 4 port – ¾"F x 4 @ ½"F x ½"F	10/Box	20
5-PORTMAN	Cast 5 port – ¾"F x 1@ ¾"F x 4 @ ½"F x ½"F	1 Ea.	2.2
5-PORTMAN-1	Cast 5 port – 1"F x 1@ ¾"F x 4 @ ½"F x ¾"F	1 Ea.	2.5
5-PORTMAN-2	Cast 5 port – 1-¼"F x 5 @ ¾"F x 1"F	1 Ea.	6.7
5-PORTMAN-3	Cast 5 port – 1-¼"F x 5 @ ½"F x 1"F	1 Ea.	5.7
4-PORTMAN-2	Cast 4 port – 1-½"F x 4 @ ¾"F x 1-½"F	1 Ea.	7.2
4-PORTMAN-3	Cast 4 port – 2"F x 4 @ 1"F x 1-½"F	1 Ea.	8.6
4-PORTMAN-M	Cast 4 port – ¾"F x 4 @ ½"F x ¾"M	1 Ea.	2.3

PROTECTION DEVICES AND BONDING CLAMPS:

APPLICATION:

- Striker plates used for protection where flexible gas piping passes through structural members and is restricted from moving to avoid nails, screws and other potential puncture threats.
- Steel conduit is used to provide additional protection where striker plates cannot be easily installed.

MATERIAL / SPECIFICATIONS:

- Striker Plates – 16 gauge AISI1050 Carbon Steel Hardened to Rc 45.
- Steel Conduit – Strip wound interlocking steel.
- Bonding clamps are listed to UL467 for use on Gastite hex fittings.



Striker Plates

PROTECTION DEVICES – STRIKER PLATES & SILICONE TAPE

Part No.	Description	Pkg. Qty.	Lbs./Box
TFM204-100	Quarter Striker Plate – 3" x 2"	100/Box	8
TFM201-50	Half Striker Plate – 3" x 7"	50/Box	18
TFM203-50	Three-Quarter Striker Plate – 3" x 8"	50/Box	20
TFM205-25	Full Striker Plate – 3" x 12"	25/Box	13.8
TFM210-10	6" x 17" Striker Plate	10/Box	19
TFM211-25	Full (Drop-in) Striker Plate – ½" & ¾" CSST	25/Box	11
TFM212-25	Full (Drop-in) Striker Plate – 1" & 1¼" CSST	25/Box	16
SIL-TAPE	Self Bonding Silicone Yellow Tape – 1" x .015" x 12 yd/roll	1 Ea.	0.3
SIL-TAPE-B	Self Bonding Silicone Black Tape – 1" x .015" x 12 yd/roll	1 Ea.	0.3