NEER™ Aluminum Entrance Caps

NEC:
Listed for Ordinary Locations

Applications

- Clamp type aluminum entrance caps for threaded or unthreaded rigid conduit, IMC or EMT service masts.

Standard Material

- ECO-100 thru ECO-101: zinc diecast
- ECO-102 thru ECO-109: aluminum/natural

NEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E302405
- NEMA: FB-1

ECO –100

Illustrated Dimensions



Trade Size (Inches)	Dimensions in Millimeters (Inches) A	B	Insulator Holes No. Holes	Dia.	Catalog Number
1/2	68.6 (2.70)	82.6 (3.25)	4	19/64	**ECO-100**
3/4	71.1 (2.80)	92.5 (3.64)	2 3	3/8 13/32	**ECO-101**
1	86.4 (3.40)	105.4 (4.15)	2 3	7/16 1/2	**ECO-102**
1-1/4	84.3 (3.32)	117.1 (4.61)	2 3	27/64 5/8	**ECO-103**
1-1/2	120.7 (4.75)	147.1 (5.79)	2 1 3	19/32 7/16 3/4	**ECO-104**
2	146.1 (5.75)	175.3 (6.90)	2 3 1	3/4 1 1-5/16	**ECO-105**
2-1/2	177.8 (7.00)	266.7 (10.50)	3 1 3	7/8 1 1-5/16	**ECO-106**
3	215.9 (8.50)	298.5 (11.75)	4 3	1-1/8 1-3/4	**ECO-107**
3-1/2	215.9 (8.50)	311.2 (12.25)	4 3	1-1/8 1-3/4	**ECO-108**
4	222.3 (8.75)	317.5 (12.50)	4 3	1-1/8 1-3/4	**ECO-109**

© February 2017

NEER™ Aluminum Entrance Caps

NEC:
Listed for Ordinary Locations

Applications

- Set screw type aluminum entrance caps for unthreaded rigid conduit or IMC service masts.

Standard Material

- Aluminum/natural

NEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E302405
- NEMA: FB-1

ECS–105

Illustrated Dimensions



	Dimensions in Millimeters (Inches)		Insulator Holes		
Trade Size (Inches)	A	B	No. Holes	Dia.	Catalog Number
2	139.7 (5.50)	177.8 (7.00)	2 3 1	3/4 1 1-5/16	**ECS-105**
2-1/2	184.2 (7.25)	260.4 (10.25)	3 1 3	7/8 1 1-5/16	**ECS-106**
3	222.3 (8.75)	273.1 (10.75)	4 3	1-1/8 1-3/4	**ECS-107**
3-1/2	235.0 (9.25)	342.9 (13.50)	4 3	1-1/8 1-3/4	**ECS-108**
4	235.0 (9.25)	342.9 (13.50)	4 3	1-1/8 1-3/4	**ECS-109**

Visit our website at **www.emerson.com** or contact us at **(800) 621-1506**.
© February 2017

EMERSON