anaco–husky

ANACO FAMILY OF COUPLINGS

Anaco is the largest manufacturer of couplings in the United States providing the perfect solution for joining hub-less cast iron pipe and fittings in drainage, waste and vent (DWV) plumbing systems as well as dissimilar piping products—**a complete coupling solution.**

PRODUCTS

- Anaco No-Hub Coupling
- Cremco Transition Coupling
  - Shielded Transition Coupling
  - Unshielded Flex Coupling
  - ARC Shielded Coupling
- Rigid Quik Coupling
- Service Weight Gaskets
- Husky CR 7000 Coupling
  - 316- SS Corrosion Resistance
- Husky SD 4000 Coupling
- Husky HD 2000 Coupling
- Husky Transition Couplings
  - SD 4200 –PVC x Cast Iron
  - SD 4100–Copper x Cast Iron
  - SD 4000 –Cast Iron Reducers

HUSKY SD 4000 COUPLINGS

Husky SD 4000 Couplings have been engineered by Anaco to provide a heavy-duty, all stainless steel coupling, balancing the desire for a more rigid joint with the need to provide a superior positive seal, which can accommodate possible disparities in the No-Hub pipe and fittings. This has been accomplished by manufacturing our coupling with a super-duty corrugated shield of sufficient width to accommodate additional surface-bearing sealing clamps.

Size	Width	# Straps	Torque
1½" to 4"	3.0	4	80
5" & 6"	4.0	6	80
8" & 10"	4.0	6	80
12" & 15"	5.5	6	80

PRODUCTS

- Husky SD 4000
- Husky SD 4200 Transition
  - PVC x CI 1½"–10"
- Husky SD 4000 Reducer
  - 2" x 1½", 3" x 2", 4" x 3", 4" x 2"
- Husky SD 4100 Transition
  - CI x Copper 2" x 1½", 2" x 2"

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
  - 4200 Meets ASTM C 1460
- ASTM C 564
- FM 1680 Class 1
- CSA B 602
- IAPMO File 6726
  - 4200 IAPMO File 5794
- 100% made in the USA
- Compliant to BAA, TAA, ARRA and NAFTA

APPLICATIONS

- Hospitals
- Universities
- Museums
- Storm Systems
- Seismic Areas
- Government
- Correctional
- Data Centers/Labs
- Sports Stadiums
- Airports
- Convention Centers
- High Rises

HUSKY CR 7000 316 STAINLESS STEEL

The Husky CR 7000 Corossion Resistant Coupling is the first 316 stainless steel, heavy-duty coupling. It balances the desire for a more rigid joint with the need to provide a superior positive seal, which can accommodate possible disparities in the no-hub pipe & fittings. Sizes: 1½"–10"

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
- ASTM C 564
- FM 1680 Class 1
- IAPMO File 6726
- 100% made in the USA

APPLICATIONS

- Corrosive Environments
- Around Waterways
- Exposed Areas
- Parking Garages
- Bridges/Tunnels
- Underground

HUSKY HD 2000 COUPLINGS

Husky HD 2000 Couplings have a slightly thinner shield than the Husky SD 4000. They consist of a 304 stainless steel shield, clamp assembly and a neoprene gasket. The 305 stainless steel 5⁄16" screw requires 80-inch pounds of torque. Sizes: 1½"–10"

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
- ASTM C 564
- FM 1680 Class 1
- CSA B 602
- IAPMO File 6726
- 100% made in the USA
- Compliant to BAA, TAA, ARRA and NAFTA

APPLICATIONS

- Hotels
- Municipal
- Casinos
- Commercial
- Industrial
- Offices

anaco STANDARD NO-HUB COUPLINGS

Anaco No-Hub couplings consist of a 300 Series stainless steel shield, clamp assembly and a Neoprene gasket. Coupling sizes range from 1½" through 15" diameters.

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- CISPI 310
- ASTM C 1277
- ASTM C 564
- NSF™ Certified
- IAPMO File 2206
- 100% made in the USA
- Compliant to BAA, TAA, ARRA and NAFTA

CREMCO Couplings by Anaco

TRANSITION COUPLINGS

PRODUCTS

- **Cremco Specialty Transition Couplings**
  - Shielded Transition Coupling
  - Unshielded Flex Coupling
  - ARC Shielded Coupling
- **Rigid Quik Unshielded Couplings** – Meets ASTM 1461

FEATURES

- Meets and exceeds material and performance requirements of ASTM C 1460
- Neoprene gaskets meet and exceed ASTM C564
- Neoprene gaskets integrate transitional design with center stop serving as noise dampening mechanism
- All 300–series stainless steel components meet ASTM A240

SERVICE WEIGHT GASKETS

PRODUCTS

- **Ty-Seal**
- **EZ-Tight**

FEATURES

- Available in sizes from 2"–15"
- Neoprene rubber meets/exceeds ASTM C564
- 100% made in the USA

Anaco-Husky ■ 1001 El Camino Avenue ■ Corona, CA 92879 ■ 951.372.2732 ■ Anaco-Husky.com