Catalog No.:_____

Job/Title:_____

Notes: _____

SPECIFICATION & FEATURES

FIRESTOP PUTTY STICK & PAD

DESCRIPTION:

Orbit Industries' Firestop Putty Pads and Sticks are hand-moldable, non-curing, fire rated material used to prevent the spread of hazards in the event of a fire. Fire Rated for up to 3 hours, the products expand when exposed to fire, preventing the passage of flame, smoke and toxic gases. Both pads and sticks will not dry out or crumble, and can be reused as penetrating items are installed or removed. *Putty Pads* are used on electrical boxes to maintain the hourly rating of fire-rated walls. In addition they help reduce sound transmission and feature a STC rating of 60. *Putty Sticks* are used to seal around penetration items such as cables, electrical conduits and metal pipes, through fire-rated walls, floors and blank openings.

FSPP67
FSPP77

FSPS18

FEATURES:

- Applied by hand with no curing time
- Pad - Soundproof with STC Rating 60*
- Intumescent @ 220 ˚F
- No Asbestos fillers or Volatile Solvents include
- Will not dry out or crumble, reusable
- Adheres to all common building surfaces
- Fire rated up to 3 hours in accordance with ASTM E814, UL 1479 and ULC/CAN4-S115-M Standards

* Tested in a UL 411 wall assembly/section to ASTM E90

CERTIFICATION:

CLASSIFIED C UL US

FM APPROVED

CONFIGURATION DATA:

Part No.	Description	Std Qty
FSPS18	FireStop Putty Stick, 18 Cu.In., Red	12
FSPP67	FireStop Putty Pad, 6"x7"x1/8", Red	20
FSPP77	FireStop Putty Pad, 7"x7"x1/8", Red	20