PTFE Tapes & Thread Sealants

Blue Monster® PTFE Thread Seal Tape - Mini-Monster Contractor Grade

Rugged, general purpose tape in a monstrous 1429" roll! Ideal for hundreds of applications.

Blue Monster is a higher-quality PTFE sealing tape that is easier to apply. Blue Monster has not been stretched during the manufacturing process, so it is thicker and creates a more effective seal with less tape, and no need for pipe dope. Use Blue Monster on threads made from galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass and more.

Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
70659	1/4" x 520"	10	100	0.5 lbs.
70660	1/2" x 260"	144	720	5.5 lbs.
70661	1/2" x 520"	144	720	7.5 lbs.
70662	3/4" x 260"	100	500	5.0 lbs.
70663	3/4" x 520"	100	500	7.0 lbs.
70664	1" x 260"	120	600	8.0 lbs.
70665	1" x 520"	120	600	11.0 lbs.
70885	1/2" x 1429"	45	270	5.5 lbs.
70886	3/4" x 1429"	27	162	5.0 lbs.
70887	1" x 1429"	27	162	5.75 lbs.
70888	2" x 1429"	27	162	11.40 lbs.

Blue Monster PTFE Thread Seal Tape is available in a point-of-sale shelf and counter display.

Listed

LISTED
PIPE JOINT TAPE
5GB4

Specifications:

Composition: 99.6% PTFE < 0.4% Pigment
Color: Blue
Thickness: 0.0035" +/-10% (0.0889 mm +/-10%)
Density: 0.8g/cm^3
Elongation: 100%
PSI rating: 10,000 PSI (69,000 kPa) water and oil
Temperature range: -450ºF to +500ºF (-268ºC to +260ºC) PTFE is completely stable up to +500ºF or +260ºC. Decomposition is slow up to +750ºF or +400ºC. Decomposition will occur on contact with naked flames.
Tensile strength: 115N/mm^2

Blue Monster® Gas Guard PTFE Thread Seal Tape

Monstrous 1000" roll! Color coded yellow for easy identification by gas companies worldwide.

Blue Monster Gas Guard PTFE thread sealing tape is designed specifically for gas lines. This is a full or maximum-density thread sealing tape. Blue Monster Gas Guard tape is approved by relevant authorities and used by the gas industry world-wide. It's color-coded yellow so fitters and inspectors can easily recognize it as an approved tape. Ideally suited for natural gas, propane and butane lines. Use on threads of approved gas piping systems. Do not use Blue Monster Gas Guard Thread Seal Tape on oxygen systems.

Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
70826	1/2" x 1000"	30	180	4.0 lbs.
70827	3/4" x 1000"	24	144	5.0 lbs.

Blue Monster Gas Guard PTFE Thread Seal Tape is available in an attractive point-of-sale shelf and counter display.

Specifications:

Composition: 99.0% PTFE <1.0% Pigment
Color: Yellow
Thickness: 0.004" +/-10% (0.102mm +/-10%)
Density: 1.5g/cm^3 +/-10%
Elongation: >100%
Temperature range: -400˚F to +500˚F (-268˚C to + 260˚C) PTFE is completely stable up to +500˚F or +260˚C. Decomposition is slow up to 750˚F or 400˚C. Decomposition will occur on contact with naked flames.
Tensile strength: 10-17 N/mm^2

Certified to comply with the provisions of MilSpec T-27730A, UL-listed, CSA approved