# SR Trace Cable Connection Kits and Accessories Specification Guide

For use in ordinary locations; not for use in hazardous locations.

**SRP**

CSA Certified Power/Splice Connection Kit. Provides heat shrink tubing based power connection for one or two cables within customer supplied junction box. Also provides heat shrinkable end seals. Can also be used for heating cable to heating cable splice using a customer supplied junction box.

**SRST**

UL Listed and CSA Certified In-line Splice Connection Kit. Provides heat shrink tubing based in-line splice connection of two or three heating cables. Junction box is not required. Each kit performs two sets of splices.

**SRES**

UL Listed and CSA Certified End Seal Kit. Provides materials necessary to perform a moisture proof end seal of the heating cable circuit. Each kit contains 5 end seals.

**SRME**

UL Listed and CSA Certified End Seal Kit. The SRME End Seal Kit is used for terminating the ends of field-fabricated heater cables. Constructed of molded silicone material with adhesive. Designed for use with all versions of EasyHeat TSR, SR and HSR heating cables. Each kit contains materials to make 5 complete terminations.

**SRMP**



UL Listed and CSA Certified Power End Connection Kit. The SRMP Power End Connection Kit is for joining field-fabricated heater cables to an electrical power cord or inside a power connection box. Constructed of molded silicone material with adhesive. Designed for use with all versions of EasyHeat TSR, SR and HSR heating cables. Each kit contains materials to make 5 complete connections.

**SRTCS**

66 feet 3/4" w. fiberglass tape and five "caution" signs for compliance with NEC 427-13.

**SRSRG**

UL Listed and CSA Certified Roof and Gutter In-line Splice Kit. Provides materials necessary to perform a splice of two roof and gutter heating cables. Each kit contains one splice.

**ZH-C**

Roof Clips and Spacers. Used to attach heating cable to roof and also to maintain cable spacing in gutters and downspouts. Each kit has components for 50 roof clips or 25 cable spacers.

**DSH**

Downspout Hanger. Used to support heating cable where it enters and exits a downspout. Each kit contains two hangers.

## PRODUCT INSTALLATION

All Easy Heat SR Trace self-regulating heating cables must be installed with appropriate connection kits. These connection kits are available from Easy Heat and contain detailed instructions for connecting the cable to the power supply and/or other heating cables. Agency Approvals (UL or CSA) are only valid when appropriate kits are used to install the heating cable for the appropriate heating application.

⚠ **WARNING!** FAILURE TO INSTALL EASY HEAT SR TRACE WITH APPROPRIATE CONNECTION KITS MAY RESULT IN FIRE, ELECTROCUTION, PIPE FREEZE-UP OR OTHER DANGEROUS CONDITIONS.

Easy Heat products are provided with a limited warranty: see owner's manual or contact Easy Heat for complete terms and conditions.



©2016 EasyHeat