FLASHSHIELD+™ CORRUGATED STAINLESS STEEL TUBING (CSST):

APPLICATION:

- CSST flexible gas piping supplies natural gas or liquefied petroleum gas to appliances.

MATERIAL / SPECIFICATIONS:

- Tubing: ASTM A240 Type 304 Stainless Steel.
- Jacket: Electrically insulative and UV resistant polymer, complying with requirements of ASTM E84 and CAN/ULC-S102.2 25/50.
- Protective jacket system, complies with ICC-ES PMG LC1027.

FEATURES AND BENEFITS:

- Electrically insulative polymer cover.
- Metallically shielded CSST.
- Protective shield is electrically continuous through fitting joints (Arc-Trap™).
- Metal shield layer dissipates and conducts electricity.
- No manufacturer required bonding.
- Flexibility means quick and easy installations. FlashShield+ installs 30-70% faster than traditional piping methods.
- Pre-marked by the foot, there's no measuring, rigid pipe cutting or threading. This means less waste and fewer fittings.
- 75% fewer fittings in the average installation means a safer system, less leak potential and reduced callbacks.
- FlashShield+ CSST is lightweight—250 feet of 1/2" CSST weighs approx. 50 lbs and can be easily transported and handled on the job.
- Call Customer Service for custom lengths of tubing and job-specific accessories.

FLASHSHIELD+ CORRUGATED STAINLESS STEEL TUBING (CSST)

Part No.	Description	Pkg. Qty.	Lbs.	Reel Size (Dia. X Width)
FSP-8-250	**1/2" FlashShield+ Corrugated Stainless Steel Tubing**	**250 Ft/Coil**	**49.5**	**20" x 12-1/2"**
FSP-8-25-5*		Box (5Coils/Box)	23	22" x 21-1/2" x 21-1/2"
FSP-8-50*		50 Ft/Box	8.3	21" x 6"
FSP-8-125		125 Ft/Coil	28.8	20" x 12-1/2"
FSP-8-500		500 Ft/Coil	95	24" x 25"
FSP-8-1000		1,000 Ft/Coil	187	32" x 21-1/2"
FSP-8-1500		1,500 Ft/Coil	270	32" x 21-1/2"
FSP-11-250	**3/4" FlashShield+ Corrugated Stainless Steel Tubing**	**250 Ft/Coil**	**64.3**	**24" x 25"**
FSP-11-25-5*		Box (5Coils/Box)	29	22" x 21-1/2" x 21-1/2"
FSP-11-50*		50 Ft/Box	10.5	21" X 6"
FSP-11-125		125 Ft/Coil	34.1	20" X 12-1/2"
FSP-11-500		500 Ft/Coil	116.5	24" x 25"
FSP-11-1000		1,000 Ft/Coil	230	32" x 21-1/2"
FSP-16-150	**1" FlashShield+ Corrugated Stainless Steel Tubing**	**150 Ft/Coil**	**58.1**	**24" x 25"**
FSP-16-50		50 Ft/Box	23.4	20" x 12-1/2"
FSP-16-75		75 Ft/Coil	31	20" x 12-1/2"
FSP-16-300		300 Ft/Coil	104.1	24" x 25"
FSP-16-500		500 Ft/Coil	174.5	32" x 21-1/2"

*Packaged in box.
Please contact Gastite Customer Service for custom lengths.

FlashShield+ ENHANCED PROTECTION

THE NEXT EVOLUTION IN CSST.

Homes are evolving, and so are the gas delivery requirements of today's homeowners. Make sure your business keeps evolving, too, by installing the industry's premium gas delivery system. FlashShield+ features all of the electrical and lightning safety you demand, plus several new innovations that make it easier to assemble and install.

RESISTS HOUSEHOLD CURRENT ARCS AND LIGHTNING

The only CSST proven to resist electrical system fault current arcs, as well as lightning strikes.

NEW LAYERS CUTS LIKE A SINGLE JACKET

New layers are bonded together with engineered adhesives, so they cut like a single jacket without the need for a special tool.

STILL THE MOST LIGHTNING RESISTANT

Meets ICC-ES PMG LC1027 standard for lightning strike protection.