THREAD SEALANTS

For more than 100 years Whitlam has provided plumbers with trusted thread sealants and thread sealant tape. Whitlam Thread Sealants are developed for most carrying systems, including air, petroleum, water, steam, gases and many chemicals. Meets codes for military, international fuel gas, and federal specifications.

pw-G/dwv/sw

TALON PTFE Thread Sealing Compound

An all-purpose, triple lubricating industrial grade thread sealing compound that contains graphite, ceramic microspheres, and virgin PTFE for optimal sealing and Freedom from Leaks™. Exceeds Federal Specification TT-S-1732. Meets International Fuel Gas Code 403.9.3 for Thread Joint Compounds. Meets ANSI LC 7-2009 for Pipe Joint Sealing Compounds and Materials. Meets CAN/ULC-S642-2010 (R2016) Standard for Compounds and Tapes for Threaded Pipe Joints. **Made in the U.S.A.**

- Zero-VOC^
- Nontoxic/Noncombustible/Non-Seizing
- Ceramic microspheres lubricate and provide a ceramic seal when threads are seated
- Excellent for stainless steel threaded connections and safe for use on PVC & CPVC

^Considered an exempt LVP-VOC compound when tested as a consumer good.

STOCK CODE	SIZE	CONTAINER	ITEMS/CASE	CASE WEIGHT
TAL4	1/4 Pint - 118 ml	Brush Top Can	24	15 lbs. - 6.8 kg
TAL8	1/2 Pint - 237 ml	Brush Top Can	24	24 lbs. - 10.9 kg
TAL8A	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg
TAL16	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg
TAL32	Quart - .95 L	Brush Top Can	12	42 lbs. - 19.1 kg
TAL5	5 Gallon - 18.9 L	Pail w/Handle	1	65 lbs. - 29.5 kg
TAL55	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg

pw-G/dwv/sw

Compatible

BLUE MAGIC Industrial Grade Pipe Thread Compound

An all-purpose, non-seizing, blue industrial grade pipe thread compound that produces a leakproof seal on all types of metal and plastic threaded connections. Exceeds Federal Specification TT-S-1732. Meets International Fuel Gas Code 403.9.3 for Thread Joint Compounds. Meets ANSI LC 7-2009 for Pipe Joint Sealing Compounds and Materials. Meets CAN/ULC-S642-2010 (R2016) Standard for Compounds and Tapes for Threaded Pipe Joints. **Made in the U.S.A.**

- Suitable for all types of metal and ABS, PVC, and CPVC threaded connections
- Excellent for stainless steel threaded connections
- Superior anti-galling properties
- Approved for use on Spears FlameGuard® CPVC Systems

IG2	2 oz. - .056 kg	Tube**	72	11 lbs. - 5.0 kg
IG4	1/4 Pint - 118 ml	Brush Top Can	24	15 lbs. - 6.8 kg
IG8	1/2 Pint - 237 ml	Brush Top Can	24	24 lbs. - 10.9 kg
IG8A	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg
IG16	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg
IG32	Quart - .95 L	Brush Top Can	12	42 lbs. - 19.1 kg
IG5	5 Gallon - 18.9 L	Pail w/Handle	1	65 lbs. - 29.5 kg
IG55	55 Gallon - 208 L	55 Gallon Drum	1	640 lbs. - 290.3 kg
IG8C*	1/2 Pint - 237 ml	Brush Top Can	24	24 lbs. - 10.9 kg
IG8CA*	1/2 Pint - 237 ml	Brush Top Can (Display Box)	12	13 lbs. - 5.9 kg
IG16C*	Pint - 473 ml	Brush Top Can	12	22 lbs. - 10.0 kg

*Bilingual Label: French and English. **Tubes Packed 12 Per Clear Plastic Tub.
FlameGuard® is a registered trademark of Spears Manufacturing Company.

Pallet Quantities for Thread Sealants: 1/4 Pint = 130 Cases, 1/2 Pint = 80 Cases, 1 Pint = 80 Cases, 1 Quart = 56 Cases, 1 Gallon = 45 Cases