Series 169L
Brass No Kink Hose Bibb, MIP Inlet

- Certified to SWDA and California AB1953
- Certified to NSF/ANSI 61-8
- 125 lb. CWP
- Cast brass
- Heavy duty construction
- Green tee handle
- ISO 9001:2008 manufacturer

Size in	Part Number	Packing		Weight lb
	Male	Inner	Master	
1/2	0190169GL	15	90	0.5
3/4	0190169IL	15	90	0.5

Series 169IGL
Brass No Kink Hose Bibb, Sweat Inlet

- Certified to SWDA and California AB1953
- Certified to NSF/ANSI 61-8
- 125 lb. CWP
- Cast brass
- Heavy duty construction
- Green tee handle
- ISO 9001:2008 manufacturer

Size in	Part Number	Packing		Weight lb
	Male / Fem SWT	Inner	Master	
3/4 x 1/2	0190169IGL	15	90	0.5

Series 120L & 125L
Washing Machine Valves

- Certified to SWDA and California AB1953
- Certified to NSF/ANSI 61-8
- 125 lb. CWP
- Cast brass
- Satin nickel finish

Size in	Part Number	Ends Config.	Packing		Weight lb
			Inner	Master	
1/2	0190120GL	FIP x MHT	12	120	0.3
5/8 OD	0190125GL	Comp x MHT	12	120	0.4

Series 161 & 162
Transition Adapter

- Brass to CPVC
- Certified to NSF/ANSI 61.9

Size in	Part Number		Packing		Weight lb
	MIP x Slip	FIP x Slip	Inner	Master	
1/2	0945161G	0945162G	50	300	0.2
3/4	0945161I	0945162I	50	300	0.2

Series 209MXL
Male Iron Pipe x Brass Sweat Dielectric Union

- Certified to SWDA and California AB1953
- Certified to NSF/ANSI 372
- Forged steel construction
- Zinc plated
- Self-centering washer
- Temperatures up to 212°F (100°C)

Size in	Part Number	Ends Config.	Packing		Weight lb
			Inner	Master	
1/2	0209MXGL	MIP x SWT	12	144	0.5
3/4	0209MXIL	MIP x SWT	12	144	0.6
1	0209MXKL	MIP x SWT	12	144	1.0

LEAD FREE

Series 209FXL
Female IPS x Brass Sweat Dielectric Union

- Certified to SWDA and California AB1953
- Certified to NSF/ANSI 372
- Forged steel construction
- Zinc plated
- Self-centering washer
- Temperatures up to 212°F (100°C)

Size in	Part Number	Ends Config.	Packing		Weight lb
			Inner	Master	
1/2	0209FXGL	FIP x SWT	12	144	0.3
3/4	0209FXIL	FIP x SWT	12	144	0.4
3/4 x 1/2	0209FXIGL	FIP x SWT	12	144	0.4
1	0209FXKL	FIP x SWT	12	120	0.6
1-1/4	0209FXLL	FIP x SWT	6	48	0.9
1-1/2	0209FXML	FIP x SWT	6	48	1.4
2	0209FXNL	FIP x SWT	6	24	2.7
2-1/2	0209FXPL	FIP x SWT	-	5	13.2
3	0209FXQL	FIP x SWT	-	5	15.6
4	0209FXTL	FIP x SWT	-	2	29.7

Series 209FFL
Female IPS x Female IPS Dielectric Union

- Certified to SWDA and California AB1953
- Certified to NSF/ANSI 372
- Forged steel construction
- Zinc plated
- Self-centering washer
- Temperatures up to 212°F (100°C)

Size in	Part Number	Ends Config.	Packing		Weight lb
			Inner	Master	
1/2	0209FFGL	FIP x FIP	10	100	0.5
3/4	0209FFIL	FIP x FIP	10	100	0.7
1	0209FFKL	FIP x FIP	5	50	1.1