CHARLOTTE PIPE AND FOUNDRY COMPANY®

ABS Foam Core Pipe

ABS Schedule 40 DWV Pipe (For Non-Pressure Applications)

NSF

ABS SCHEDULE 40 FOAM CORE (BLACK) PLAIN END ASTM F 628						
PART NO.	NOM. SIZE	UPC # 611942-	QTY. PER SKID (FT.)	AVG. OD (IN.)	MIN. WALL (IN.)	WT. PER 100 FT. (LBS.)
ABS 3112	1½″ x 10′	03132	2590	1.900	0.145	27.1
ABS 3112	1½″ x 20′	03133	5180	1.900	0.145	27.1
ABS 3200	2″ x 10′	03134	1670	2.375	0.154	37.7
ABS 3200	2″ x 20′	03135	3340	2.375	0.154	37.7
ABS 3300	3″ x 10′	03136	750	3.500	0.216	74.5
ABS 3300	3″ x 20′	03137	1500	3.500	0.216	74.5
ABS 3400	4″ x 10′	03138	480	4.500	0.237	107.1
ABS 3400	4″ x 20′	03139	960	4.500	0.237	107.1
ABS 3600	6″ x 10′	03140	200	6.625	0.280	187.8
ABS 3600	6″ x 20′	03141	400	6.625	0.280	187.8

NSF Listed. Meets All Requirements of ASTM F 628.

MADE IN USA

NOTICE

NOT FOR PRESSURE

Do not use ABS / ABS Plus® / PVC cellular core (foam core) pipe for pressure applications. The use of cellular core pipe in pressure applications may result in system failure and property damage.

⚠ WARNING

Testing with or use of compressed air or gas in ABS / CPVC / PVC pipe or fittings can result in explosive failures and cause severe injury or death.

- NEVER test with or transport/store compressed air or gas in ABS / CPVC / PVC pipe or fittings.
- NEVER test ABS / CPVC / PVC pipe or fittings with compressed air or gas, or air over water boosters.
- ONLY use ABS / CPVC / PVC pipe or fittings for water or approved chemicals.
- Refer to warnings on PPFA's website and ASTM D 1785.