Features & Applications

The 006e3™ ECM circulator: Three settings. One reputation.

- 13' Shut-off head, 11 gpm max flow
- Easy to use dial:
  - Low, Medium, High
  - 003 & 006 performance point references
- Rugged high-performance composite casing
- 3 color LED indicator light:
  - Blue: Operating mode
  - White: ***SureStart***®
  - Red: Error diagnostic
- Whisper quiet operation
- 1" union connection with optional ½" & ¾" fitting sets sold separately (See chart below)
- Double insulated, no ground wire required

Replacement Chart

Taco	Grundfos	Armstrong	B&G / Xylem	Laing
003 006	UP 15-18 UP 15-10 UP 10-16	Astro 225 BS Astro 225 SSU Astro 220 SSU	ecocirc e^3-4 ecocirc e^3-6 NBF-8, 9, 10, 12 SSF-9, 12	E1 Series E3 Series

Setting Selection Guide

Based on ¾" supply, ½" return copper pipe



HIGH — 500 ft pipe



MEDIUM — 350 ft pipe



LOW — 200 ft pipe or less

NOTE: Figures are for reference purposes only. Refer to ASTM guidelines for piping flow & velocity standards. For PEX, refer to pipe manufacturer guidelines.

Choose the right fitting for the job!

Image	Fitting Assembly Description	Product Code
	½" Union Sweat	UFS-050S
	½" Union FNPT	UFS-050T
	½" Union Press	UFS-050P
	¾" Union Sweat	UFS-075S
	¾" Union FNPT	UFS-075T
	¾" Union Press	UFS-075P

Fitting sets include (2) gaskets, (2) union nuts and (2) tail pieces.