PROTECTION DEVICES AND BONDING CLAMPS CONTINUED:

Steel Conduit

PROTECTION DEVICES – STEEL CONDUIT COILS

Part No.	Description	Pkg. Qty.	Lbs./Coil
FLOPPY12	¾" Coil steel conduit – Fits ⅜" CSST	50 Ft/Coil	8.4
FLOPPY16	1" Coil steel conduit – Fits ½" CSST	50 Ft/Coil	13.1
FLOPPY20	1-¼" Coil steel conduit – Fits ¾" CSST	25 Ft/Coil	11
FLOPPY24	1-½" Coil steel conduit – Fits 1" CSST	25 Ft/Coil	13.1
FLOPPY28	1-¾" Coil steel conduit – Fits 1-¼" CSST	25 Ft/Coil	16.5
FLOPPY36	2-¼" Coil steel conduit – Fits 1-½" CSST	25 Ft/Coil	28.2
FLOPPY48	3" Coil steel conduit – Fits 2" CSST	25 Ft/Coil	36

Bonding Clamp

PROTECTION DEVICES – STEEL CONDUIT COILS

Part No.	Description	Pkg. Qty.	Lbs./Box
LFLOPPY-12-50	¾" – Cut to 1 foot length – Fits ⅜" CSST	50/Box	9.3
LFLOPPY-16-50	1" – Cut to 1 foot length – Fits ½" CSST	50/Box	19
LFLOPPY-20-25	1-¼" – Cut to 1 foot length – Fits ¾" CSST	25/Box	11.8
LFLOPPY-24-25	1-½" – Cut to 1 foot length – Fits 1" CSST	25/Box	14.4
LFLOPPY-28-25	1-¾" – Cut to 1 foot length – Fits 1-¼" CSST	25/Box	17
LFLOPPY-36-25	2-¼" – Cut to 1 foot length – Fits 1-½" CSST	25/Box	28.8
LFLOPPY-48-25	3" – Cut to 1 foot length – Fits 2" CSST	25/Box	37

BONDING CLAMPS

Part No.	Description	Pkg. Qty.	Lbs./Box
CWP1JSH	Bonding Clamp for ⅜" and ½" CSST	1 Ea.	0.16
CWP2JSH	Bonding Clamp for ¾", 1" and 1-¼" CSST	1 Ea.	0.34
CWP3JSH	Bonding Clamp for 1-½" and 2" CSST	1 Ea.	1.02

SHUT-OFF VALVES, QUICK CONNECT AND ACCESSORIES:

APPLICATION:

- Ball Valves are used to control gas flow to appliances and pounds-to-inches regulator.
- Quick-Connect valve and accessories provide a safe and easy "quick-connect" for barbecue grills, space heaters and decorative lighting.

MATERIAL / SPECIFICATIONS:

- Ball Valve - ANSI/ASME B16.33.
- Quick Connect and Accessories – ANSI Z21.15, CAN 9.1,9.2, 6.9 and AGA/CGA 7-90/CR94-001.

Ball Valve

90˚ Ball Valve

SHUT-OFF VALVES

Part No.	Description	Pkg. Qty.	Lbs./Box
T100-1/2-20	½" Ball Valve rated to 125 PSI	20/Box	10
T100-3/4-10	¾" Ball Valve rated to 125 PSI	10/Box	8
T100-1-1/4-5	1-¼" Ball Valve rated to 125 PSI	5/Box	11
T90-1/2-10	½" 90 Degree Shut-Off Valve	10/Box	4.6
T90-3/4-10	¾" 90 Degree Shut-Off Valve	10/Box	7.7

Outdoor Flex Connector

OUTDOOR FLEX CONNECTOR WITH QUICK CONNECT PLUG

Part No.	Description	Pkg. Qty.	Lbs./Ea.
OUTFLEX-3/8	⅜" Outdoor Flex Connector, 10-ft, ⅜" Male plug x ⅜" Female Flare Swivel, ⅜" MPT adapter (43 CFH)*	1 Ea.	2.2
OUTFLEX-1/2	½" Outdoor Flex Connector, 10-ft, ½" Male plug x ½", Female Flare Swivel, ½" MPT adapter (87 CFH)*	1 Ea.	3.2

***Capacity of flex connector and QC valve combination, @ 1" w.c. pressure drop**

QC Valve

QC Valve Box (PVC)

Quick Connect Valves

Part No.	Description	Pkg. Qty.	Lbs./Ea.
T103029	⅜" Quick Connect Valve, 90 deg, ½" FPT inlet	1 Ea.	1
T104023	½" Quick Connect Valve, Straight, ½" FPT inlet	1 Ea.	1
QCBOXPW	⅜" QC Valve Box (white PVC) ½" FPT inlet, Surface Mount, Lockable Door	1 Ea.	1.6
QCBOXPG	⅜" QC Valve Box (grey PVC) ½" FPT inlet, Surface Mount, Lockable Door	1 Ea.	1.6
QCBOXSS	⅜" QC Valve Box (S.S.) ½" FPT inlet, Recessed, Lockable Door	1 Ea.	2.3
BBQ-SS-50	½" QC Valve Box (S.S.) ½" FPT inlet, Surface Mount, Lockable Door	1 Ea.	2

QC Valve Box (SS) Recessed

QC Valve Box (SS)